

```
R R R R R R R R R R R M M M M M M S S S S S S S S S S S
R R R R R R R R R R R M M M M M M S S S S S S S S S S S
R R R R R R R R R R R M M M M M M S S S S S S S S S S S
R R R      .   R R R M M M M M M     M M M M M M S S S
R R R          R R R M M M M M M     M M M M M M S S S
R R R          R R R M M M M M M     M M M M M M S S S
R R R          R R R M M M           M M M       M M M S S S
R R R          R R R M M M           M M M       M M M S S S
R R R          R R R M M M           M M M       M M M S S S
R R R R R R R R R R R M M M             M M M S S S S S S S S S
R R R R R R R R R R R M M M             M M M S S S S S S S S
R R R R R R R R R R R M M M             M M M S S S S S S S S
R R R        R R R    M M M             M M M               S S S
R R R        R R R    M M M             M M M               S S S
R R R        R R R    M M M             M M M               S S S
R R R            R R R M M M             M M M               S S S
R R R            R R R M M M             M M M               S S S
R R R            R R R M M M             M M M               S S S
R R R                R R R M M M         M M M S S S S S S S S S
R R R                R R R M M M         M M M S S S S S S S S
R R R                R R R M M M         M M M S S S S S S S S
```

— 52

Syn

NTS

NTS
NTS

NTS

NTS
NTS

NTS

NTS
NTS

NTS

NTS

NTS
NTS

NTS

NTS
NTS

NTS

NTS

NTS
NTS

NTS

NTS
NTS

NTS

NTS

NTS
NTS

NTS

NTS

NTS
NTS

NTS

NTS

NTS
NTS

107

NTS

NTS
NTSNT
NT

NTS

NY
RI

11

10

10

10

10

1

11. *Journal of the American Medical Association*, 273, 1995, 1033-1034.

1

RRRRRRRR	MM	MM	SSSSSSSS	IIIIII	NN	NN	TTTTTTTTTT	DDDDDDDD	EEEEEEEEEE	FFFFFFFFFF
RRRRRRRR	MM	MM	SSSSSSSS	IIIIII	NN	NN	TTTTTTTTTT	DDDDDDDD	EEEEEEEEEE	FFFFFFFFFF
RR	RR	MMM	SS	II	NN	NN	TT	DD	EE	FF
RR	RR	MMM	SS	II	NN	NN	TT	DD	EE	FF
RR	RR	MM	SS	II	NNNN	NN	TT	DD	EE	FF
RR	RR	MM	SS	II	NNNN	NN	TT	DD	EE	FF
RRRRRRRR	MM	MM	SSSSSS	II	NN	NN	TT	DD	EEEEEEEE	FFFFFFFF
RRRRRRRR	MM	MM	SSSSSS	II	NN	NN	TT	DD	EEEEEEEE	FFFFFFFF
RR	RR	MM	SS	II	NN	NN	TT	DD	EE	FF
RR	RR	MM	SS	II	NN	NNNN	TT	DD	EE	FF
RR	RR	MM	SS	II	NN	NNNN	TT	DD	EE	FF
RR	RR	MM	SS	II	NN	NN	TT	DD	EE	FF
RR	RR	MM	SSSSSSSS	IIIIII	NN	NN	TT	DDDDDDDD	EEEEEEEEEE	FFFFFFFF
RR	RR	MM	SSSSSSSS	IIIIII	NN	NN	TT	DDDDDDDD	EEEEEEEEEE	FFFFFFFF

....
....
....
....

LL	SSSSSSSS	TTTTTTTTTT
LL	SSSSSSSS	TTTTTTTTTT
LL	SS	TT
LL	SS	TT
LL	SS	TT
LL	SS	TT
LL	SSSSSS	TT
LL	SSSSSS	TT
LL	SS	TT
LL	SS	TT
LL	SS	TT
LL	SS	TT
LLLLLLLLLL	SSSSSSSS	TT
LLLLLLLLLL	SSSSSSSS	TT

M 16
15-Sep-1984 22:56:58
15-Sep-1984 22:56:57

VAX-11 Bliss-32 V4.0-742
_S255SDUA28:[RMS.OBJ]RMSINTDEF.R32;1

Page 1
(1)

++

UTLDEF.B32 - UTILITY DEFINITION MACROS FOR BLISS PROCESSING
OF STARLET DEFINITION MACROS.
Version 'V04-000'

--

```
*****
*
* COPYRIGHT (c) 1978, 1980, 1982, 1984 BY
* DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.
* ALL RIGHTS RESERVED.
*
* THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED
* ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE
* INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER
* COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY
* OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY
* TRANSFERRED.
*
* THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE
* AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT
* CORPORATION.
*
* DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS
* SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.
*****
```

++

MODIFIED BY:

V02-001 REFORMAT

Maria del C. Nasr

01-Aug-1980

--

macros to extract offsets, field widths, etc., from field extraction macros

```
MACRO $BYTEOFFSET (OFFSET, POSITION, WIDTH, SIGN) = OFFSET%;
MACRO $BITPOSITION (OFFSET, POSITION, WIDTH, SIGN) = POSITION%;
MACRO $FIELDWIDTH (OFFSET, POSITION, WIDTH, SIGN) = WIDTH%;
MACRO $EXTENSION (OFFSET, POSITION, WIDTH, SIGN) = SIGN%;
MACRO $FIELDMASK (OFFSET, POSITION, WIDTH, SIGN) =
(1^(POSITION+WIDTH) - 1^POSITION)%;
```

macro to generate eqlst constructs

MACRO

B 1
15-Sep-1984 22:56:58
15-Sep-1984 22:56:57

VAX-11 Bliss-32 V4.0-742
_S255SDUA28:[RMS.OBJ]RMSINTDEF.R32;1 Page 2
(1)

.. M 0058 0
.. M 0059 0
.. M 0060 0
.. M 0061 0
.. M 0062 0
.. 0063 0
.. 0064 0
.. M 0065 0
.. 0066 0
.. M 0067 0
.. 0068 0
.. M 0069 0
.. 0070 0

```
$EQLST(P,G,I,S)[A]=
  %NAME(P,GET1ST_A) =
    %IF NUL2ND_A
      %THEN (I) * %COUNT*(S) ! assumes i, s always generated by conversion program
    %ELSE GET2ND_A
      %FI %,
GET1ST_(A,B)=
  A %,
GET2ND_(A,B)=
  B %, ! known non-null
NUL2ND_(A,B)=
  %NULL(B) %;
```


C 1
15-Sep-1984 22:56:58
15-Sep-1984 22:56:57

VAX-11 Bliss-32 V4.0-742
_S255\$DUA28:[RMS.OBJ]RMSINTDEF.R32;1

Page 3
(2)

\$BEGIN RMSIDXMAC,V04-000

MACRO DEFINITIONS FOR RMS-32 INDEX FILE ORGANIZATION

```
*****
*
* COPYRIGHT (c) 1978, 1980, 1982, 1984 BY
* DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.
* ALL RIGHTS RESERVED.
*
* THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED
* ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE
* INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER
* COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY
* OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY
* TRANSFERRED.
*
* THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE
* AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT
* CORPORATION.
*
* DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS
* SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.
*
*****
```

++

FACILITY: RMS32 INDEX SEQUENTIAL FILE ORGANIZATION

ABSTRACT:

ENVIRONMENT:

VAX/VMS OPERATING SYSTEM

--

AUTHOR: D. H. Gillespie CREATION DATE: 17-MAR-1978
 and W. Koenig

MODIFIED BY:

V03-002 MCN0003 Maria del C. Nasr 15-Mar-1982
 Use new general linkage for RM\$BUG3. Take out definition
 for R_REC_SIZE, and R_VBN.

V03-001 MCN0002 Maria del C. Nasr 25-Mar-1982
 Add macro definition to calculate key buffer address.

V02-003 CDS0001 C Saether 9-Dec-1981
 Comment out references to CSH\$M_READAHEAD flag in the
 \$CSHFLAGS macro.

D 1
15-Sep-1984 22:56:58
15-Sep-1984 22:56:57

VAX-11 Bliss-32 V4.0-742
_S255\$DUA28:[RMS.OBJ]RMSINTDEF.R32;1

Page 4
(2)

: 0128 0
: 0129 0
: 0130 0
: 0131 0
: 0132 0
: 0133 0

V02-002 MCN0001 Maria del C. Nasr 22-Apr-1981
Add macro definition for determining record identifier size

! **


```

0134 0 | Define macro for psect attributes
0135 0 |
0136 0 |
0137 0 | MACRO PSECT_ATTR = EXECUTE,PIC,GLOBAL %;
0138 0 |
0139 0 | Define macro to extract size
0140 0 |
0141 0 | MACRO $BYTESIZE(OFFSET,POSITION,WIDTH,SIGN) = WIDTH / 8 %;
0142 0 |
0143 0 |
0144 0 | Structure declarations used for system defined structrues to save typing
0145 0 |
0146 0 | STRUCTURE
0147 0 |     BBLOCK [O, P, S, E; N] =
0148 0 |         [N]
0149 0 |         (BBLOCK+O)<P,S,E>,
0150 0 |
0151 0 |     BBLOCKVECTOR [I, O, P, S, E; N, BS] =
0152 0 |         [N*BS]
0153 0 |         (BBLOCKVECTOR+(O+I*BS))<P,S,E>;
0154 0 |
0155 0 |
0156 0 | ***** The following two macros violate the BLISS language definition
0157 0 | ***** in that they make use of the value of SP while building the argument
0158 0 | ***** list. It is the opinion of the BLISS maintainers that this usage is safe
0159 0 | ***** from planned future optimizations.
0160 0 |
0161 0 | Macro to call the change mode to kernel system service.
0162 0 |
0163 0 | Macro call format is 'KERNEL_CALL( ROUTINE, ARG1, ARG2, ...).
0164 0 |
0165 0 | MACRO
0166 0 |     KERNEL_CALL (R) =
0167 0 |         BEGIN
0168 0 |             EXTERNAL ROUTINE SYS$CMKRNL : ADDRESSING_MODE (ABSOLUTE):
0169 0 |             BUILTIN SP;
0170 0 |             SYS$CMKRNL(4, SP, %LENGTH-1
0171 0 |                 %IF %LENGTH GTR 1 %THEN, %REMAINING %FI)
0172 0 |             END%;
0173 0 |
0174 0 |
0175 0 | macro to generate a string descriptor
0176 0 |
0177 0 | MACRO
0178 0 |     DESCRIPTOR (STRING) =
0179 0 |         UPLIT (%CHARCOUNT (STRING), UPLIT BYTE (STRING))%;
0180 0 |
0181 0 |
0182 0 | macro to return the number of actual parameters supplied to a routine call
0183 0 |
0184 0 | MACRO
0185 0 |     ACTUALCOUNT =
0186 0 |         BEGIN
0187 0 |             BUILTIN AP;
0188 0 |             (.AP)<0,8>
0189 0 |             END
0190 0 |             %;

```

F 1
15-Sep-1984 22:56:58
15-Sep-1984 22:56:57

VAX-11 Bliss-32 V4.0-742
_S255\$DUA28:[RMS.OBJ]RMSINTDEF.R32;1 Page 6
(3)

```
0191 0      !
0192 0      ! macro to generate call to bug check routine
0193 0
M 0194 0      MACRO BUG_CHECK =
M 0195 0          (LINKAGE L JSB;
M 0196 0            EXTERNAL ROUTINE
M 0197 0              RMSBUG3 : RLJSB;
0198 0              RMSBUG3 ( ) %;
0199 0
0200 0      !
0201 0      ! Macro used to determine record identifier size (byte or word) depending on
0202 0      ! prologue version of the file.
0203 0
M 0204 0      MACRO IRC$ ID(RECADR) =
M 0205 0          (IF .IFAB[IFB$B_PLG_VER] LSSU PLG$C_VER_3
M 0206 0              THEN
M 0207 0                  .RECADR[IRC$B_ID]
M 0208 0              ELSE
0209 0                  .RECADR[IRC$W_ID]) % ;
0210 0
0211 0
0212 0      ! Macro used to determine address of key buffer wanted. Parameter is
0213 0      ! the keybuffer number.
0214 0      !
0215 0
M 0216 0      MACRO KEYBUF_ADDR(KBUFNO) =
0217 0          .IRAB[IRB$L_KEYBUF] + .IFAB[IFB$W_KBUFSZ] * ((KBUFNO) - 1) % ;
0218 0
0219 0
```


!KEEP THESE DEFINITIONS IN ALPHABETICAL ORDER, PLEASE!

internal register definitions

common register definitions

MACRO

COMMON_FABREG =
R_FAB, R_IFAB, R_IFAB_FILE, R_IMPURE %,

COMMON_IOREG =
R_BDB, R_BKT_ADDR %,

COMMON_RABREG =
R_RAB, R_IRAB, R_IFAB, R_IMPURE%,

COMMON_FAB_STR =
R_FAB_STR,
R_IFAB_STR,
R_IFAB_FILE_STR,
R_IMPURE_STR %,

COMMON_IO_STR =
R_BDB_STR,
R_BKT_ADDR_STR %,

COMMON_RAB_STR =
R_RAB_STR,
R_IRAB_STR,
R_IFAB_STR,
R_IMPURE_STR%;

miscellaneous register definitions

the macros associated with registers will follow these conventions:

macro r_name =
name = register_number %; (no trailing punctuation)
to be used basically in a linkage statement, and

macro r_name_str =
r_name : ref bblock %; (or whatever structure)
to be used basically in external or global register declarations

MACRO

R_BDB =
BDB = 4 %,

R_BKT_ADDR =
BKT_ADDR = 5 %,

R_FAB =
FAB = 8 %,

R_IDX_DFN =
IDX_DFN = 7 %,

R_IFAB_FILE =
IFAB_FILE = 9 %,

R_IMPURE =
IMPURE = 11 %,

R_IRAB =

H 1
15-Sep-1984 22:56:58
15-Sep-1984 22:56:57

VAX-11 Bliss-32 V4.0-742
_S255\$DUA28:[RMS.OBJ]RMSINTDEF.R32;1 Page 8
(4)

0277 0
M 0278 0
0279 0
M 0280 0
0281 0
M 0282 0
0283 0
0284 0
0285 0
M 0286 0
0287 0
M 0288 0
0289 0
M 0290 0
0291 0
M 0292 0
0293 0
M 0294 0
0295 0
M 0296 0
0297 0
M 0298 0
0299 0
M 0300 0
0301 0
M 0302 0
0303 0
M 0304 0
0305 0
M 0306 0
0307 0
M 0308 0
0309 0
0310 0

R_RAB = IRAB = 9 %,
R_REC_ADDR = RAB = 8 %,
R_IFAB = REC_ADDR = 6 %,
IFAB = 10 %,

R_BDB_STR =
R_BDB : REF BBLOCK %,
R_BKT_ADDR_STR =
R_BKT_ADDR : REF BBLOCK %,
R_FAB_STR =
R_FAB : REF BBLOCK %,
R_ID_STR =
R_ID : BYTE %,
R_IDX_DFN_STR =
R_IDX_DFN : REF BBLOCK %,
R_IFAB_STR =
R_IFAB : REF BBLOCK %,
R_IMPURE_STR =
R_IMPURE : REF BBLOCK %,
R_IRAB_STR =
R_IRAB : REF BBLOCK %,
R_RAB_STR =
R_RAB : REF BBLOCK %,
R_REC_ADDR_STR =
R_REC_ADDR : REF BBLOCK %,
R_IFAB_FILE_STR =
R_IFAB_FILE : REF BBLOCK %,
R_VBN_STR =
R_VBN %;


```

0311 0
0312 0
0313 0
0314 0
0315 0
0316 0
0317 0
0318 0
0319 0
0320 0
0321 0
0322 0
0323 0
0324 0
0325 0
0326 0
0327 0
0328 0
0329 0
0330 0
0331 0
0332 0
0333 0
0334 0
0335 0
0336 0
0337 0
0338 0
0339 0
0340 0
0341 0
0342 0
0343 0
0344 0
0345 0
0346 0
0347 0
0348 0
0349 0
0350 0
0351 0
0352 0
0353 0
0354 0
0355 0
0356 0
0357 0
0358 0
0359 0
0360 0

|      macro to make the status codes small
|
|      MACRO WORDMASK(CODE) = (
|          (CODE AND %X'FFFF'))
|          %;
|
|      MACRO RMSERR (CODE) = (
|          %NAME('RMS$_',CODE) AND %X'FFFF')
|          %;
|
|          RMSSUC (CODE) = (
|              %IF %LENGTH EQL 0 %THEN
|                  1
|              %ELSE
|                  %NAME('RMS$_',CODE) AND %X'FFFF'
|              %FI)
|          %;
|
|      macro to make constants that are calculated have the <0,16> attribute
|
|      macros to make the code a little nicer
|
|      MACRO
|
|      this macro allows you to make a call to another routine
|      (and do whatever you want in a block before the call),
|      and if an error resulted, do whatever you want and
|      then return with the status.
|
|      RETURN_ON_ERROR (CALL) [] =
|          (LOCAL STATUS;
|           IF NOT (STATUS = (CALL)) THEN
|               (%REMAINING;
|                RETURN .STATUS)) %;
|
|      this macro is the same as the one above, except that it
|      it returns w/ status whether or not there was an error
|      and the caller can supply an 'else' block
|      note: the 'call' part and 'else' part must be separated by a comma
|      not a semicolon and the 'else' part must be terminated by a semicolon
|
|      RETURN_ELSE (CALL) [] =
|          (LOCAL STATUS;
|           IF NOT (STATUS = (CALL)) THEN RETURN .STATUS
|           ELSE
|               %REMAINING
|               RETURN .STATUS)
|
|      %;

```

```

0361 0 ! this is an internal cache macro to put the value of the flags into cshtmp
M 0362 0 MACRO IRP(A)[] =
M 0363 0     %ASSIGN (CSHTMP,CSHTMP OR %NAME('CSH$M_',A));
M 0364 0     IRP(%REMAINING);
0365 0     %;
0366 0
0367 0 ! this is an internal cache macro to verify the cache flags and set them up
M 0368 0 MACRO $CSHFLAGS(FLAGS) =
M 0369 0     COMPILETIME CSHTMP = 0;
M 0370 0     %IF NOT %NULL(FLAGS) %THEN
M 0371 0         IRP (%REMOVE(FLAGS));
M 0372 0     %FI;
M 0373 0     %IF (CSHTMP AND CSH$M_READAHEAD) NEQ 0 %THEN
M 0374 0         %ASSIGN (CSHTMP,CSHTMP OR CSH$M_NOWAIT);
M 0375 0         %IF (CSHTMP AND
M 0376 0             (CSH$M_LOCK OR CSH$M_NOREAD OR CSH$M_NOBUFFER))
M 0377 0             NEQ 0 %THEN
M 0378 0             %ERRORMACRO ('INVALID CACHE FLAG COMBINATION');
M 0379 0         %FI;
M 0380 0     %FI;
M 0381 0     %IF (CSHTMP AND CSH$M_NOBUFFER) NEQ 0 %THEN
M 0382 0         %ASSIGN (CSHTMP,CSHTMP OR CSH$M_NOREAD);
M 0383 0     %FI;
M 0384 0     %;
0385 0
0386 0 ! this is a macro to call cache or cached
0387 0 MACRO CACHE (VBN,SIZE,FLAGS,EP) =
M 0388 0     BEGIN
M 0389 0         %IF %NULL(FLAGS) %THEN
M 0390 0             COMPILETIME CSHTMP = 0
M 0391 0         %ELSE
M 0392 0             $CSHFLAGS(FLAGS)
M 0393 0         %FI;
M 0394 0         %IF %NULL(EP) %THEN
M 0395 0             RM$CACHE(VBN,SIZE,CSHTMP)
M 0396 0         %ELSE
M 0397 0             %NAME('RM$CACHE',EP)(VBN,SIZE,CSHTMP)
M 0398 0         %FI
M 0399 0     END
M 0400 0     %;
0401 0
0402 0 ! this is a macro to call getbkt or getbktc
0403 0 MACRO GETBKT (VBN,SIZE,FLAGS,EP) =
M 0404 0     BEGIN
M 0405 0         %IF %NULL(FLAGS) %THEN
M 0406 0             COMPILETIME CSHTMP = 0
M 0407 0         %ELSE
M 0408 0             $CSHFLAGS(FLAGS)
M 0409 0         %FI;
M 0410 0         %IF %NULL(EP) %THEN
M 0411 0             RM$GETBKT(VBN,SIZE,CSHTMP)
M 0412 0         %ELSE
M 0413 0             %NAME('RM$GETBKT',EP)(VBN,SIZE,CSHTMP)
M 0414 0         %FI
M 0415 0     END
M 0416 0
M 0417 0

```


K 1
15-Sep-1984 22:56:58
15-Sep-1984 22:56:57

VAX-11 Bliss-32 V4.0-742
_S255SDUA28:[RMS.OBJ]RMSINTDEF.R32;1 Page 11
(6)

: 0418 0
: 0419 0
: 0420 0
: 0421 0

%;

L 1
15-Sep-1984 22:56:58
15-Sep-1984 22:56:57

VAX-11 Bliss-32 V4.0-742
_S255\$DUA28:[RMS.OBJ]RMSINTDEF.R32;1 Page 12
(7)

! these are macros to do probing of user structures

MACRO

IFNORD (SIZE,ADDR,MODE) [] =

(

IF NOT PROBER(

%IF %NULL(MODE) %THEN 0 %ELSE MODE %FI,

SIZE,

ADDR)

THEN

%REMAINING)

%,

IFNOWRT (SIZE,ADDR,MODE) [] =

(

IF NOT PROBEW(

%IF %NULL(MODE) %THEN 0 %ELSE MODE %FI,

SIZE,

ADDR)

THEN

%REMAINING)

%,

IFRD (SIZE,ADDR,MODE) [] =

(

IF PROBER(

%IF %NULL(MODE) %THEN 0 %ELSE MODE %FI,

SIZE,

ADDR)

THEN

%REMAINING)

%,

! macros to do long probes

READ_LONG(SIZE,ADDR,MODE) = NOT RM\$NOREAD_LONG(SIZE,ADDR,MODE) %,

WRT_LONG(SIZE,ADDR,MODE) = NOT RM\$NOWRT_LONG(SIZE,ADDR,MODE) %;


```

0459 0      | macro to release a bucket and clear the location where its bdb addr is stored
0460 0
0461 0
M 0462 0      | MACRO RELEASE(B) =
MM 0463 0      |     BEGIN
MM 0464 0      |     BDB = .B;
MM 0465 0      |     B = 0;
M 0466 0      |     RMSRL$BKT(0);
0467 0      |     END%;
0468 0
0469 0      | macro to make sure that an assumption made about the position of symbols
0470 0      | in a structure is still valid
0471 0      | the arguments to this macro must be preceded by %quote
0472 0      | e.g., assume (%quote ifb$b_bid, %quote ifb$b_bln);
0473 0
M 0474 0      | MACRO ASSUME (A,B) =
MM 0475 0      |     %IF $BYTEOFFSET(A) + $BYTESIZE(A) NEQ $BYTEOFFSET(B)
MM 0476 0      |     %THEN %WARN('WARNING CONSTANT HAS CHANGED')
0477 0      |     %FI %;
0478 0
0479 0      | this version of assume is good for constants
0480 0      | e.g. assume (irc$c_fixovhdsz + 2, irc$c_varovhdsz);
0481 0
M 0482 0      | MACRO ASSUME C (A,B) =
MM 0483 0      |     %IF $BYTEOFFSET(A) NEQ $BYTEOFFSET(B)
MM 0484 0      |     %THEN %WARN('WARNING CONSTANT HAS CHANGED')
0485 0      |     %FI %;
0486 0      |     [ 2 0 1 , 1 0 ] R M S I D X L N K . R 3 2
0487 0      |
0488 0      | Define subroutine linkage
0489 0
0490 0
0491 0      | *****
0492 0      | *
0493 0      | * COPYRIGHT (c) 1978, 1980, 1982, 1984 BY
0494 0      | * DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.
0495 0      | * ALL RIGHTS RESERVED.
0496 0      | *
0497 0      | * THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED
0498 0      | * ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE
0499 0      | * INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER
0500 0      | * COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY
0501 0      | * OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY
0502 0      | * TRANSFERRED.
0503 0      | *
0504 0      | * THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE
0505 0      | * AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT
0506 0      | * CORPORATION.
0507 0      | *
0508 0      | * DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS
0509 0      | * SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.
0510 0      | *
0511 0      | *
0512 0      | *****
0513 0
0514 0      | ++
0515 0

```

N 1
15-Sep-1984 22:56:58
15-Sep-1984 22:56:57

VAX-11 Bliss-32 V4.0-742
_\$255\$DUA28:[RMS.OBJ]RMSINTDEF.R32;1

Page 14
(8)

0516 0
0517 0
0518 0
0519 0
0520 0
0521 0
0522 0
0523 0
0524 0
0525 0
0526 0
0527 0
0528 0
0529 0
0530 0
0531 0
0532 0
0533 0
0534 0
0535 0
0536 0
0537 0
0538 0
0539 0
0540 0
0541 0
0542 0
0543 0
0544 0
0545 0
0546 0
0547 0
0548 0
0549 0
0550 0
0551 0
0552 0
0553 0

FACILITY: RMS32 INDEX SEQUENTIAL FILE ORGANIZATION

ABSTRACT: This module defines all the routine linkage

ENVIRONMENT:
VAX/VMS OPERATING SYSTEM

AUTHOR: D. H. Gillespie CREATION DATE: 17-MAR-1978
and W. Koenig

MODIFIED BY:

V03-024 RAS0154 Ron Schaefer 2-May-1983
Add NOPRESERVE (R2) to L_EXTEND0 linkage.

V03-023 MCN0020 Maria del C. Nasr 07-Apr-1983
Eliminate linkages of RMSNULLKEY, and RMSCOMPRESS KEY.
They will be using general linkages. Modify L_ACLOC3,
and L_EXTEND0 to use parameters instead of global registers.

V03-022 MCN0019 Maria del C. Nasr 05-Apr-1983
Preserve all registers except R0 and R1 in linkage
FABREG. RMSXSUM0 requires a separate linkage because
it cannot preserve R4.

V03-021 TMK0001 Todd M. Katz 26-Mar-1983
Add the linkage RABREG_4.

V03-020 MCN0018 Maria del C. Nasr 24-Mar-1983
Define new general linkages. Also, since the linkages
have changed so much, eliminate all history comments.

This module defines all the routine linkage for RMS-32 index file organization.

KEEP THESE DEFINITIONS IN ALPHABETICAL ORDER PLEASE

The following conventions will be used for linkage macros:

```
MACRO L_NAME =
    RL$NAME =
    JSB (REGISTERS) :
    GLOBAL (REGISTER DEFINITIONS) %;
```

The register definitions are macros of the forms
COMMON FABREG, COMMON RABREG, COMMON IOREG, etc.
or R_REGNAME as described in RMSIDXMAC.R32

MACRO

```
L_ALDBUF =
    RL$ALDBUF =
    JSB (REGISTER = 5) :
    GLOBAL (R_IMPURE, R_IFAB)
    NOPRESERVE (2,3,4)
    NOTUSED (8,9) %;
```

```
L_ALLOC3 =
    RL$ALLOC3 =
    JSB (REGISTER = 7; REGISTER = 1, REGISTER = 2) :
    GLOBAL (R_IFAB) %;
```

```
L_BDBALLOC =
    RL$BDBALLOC =
    JSB (REGISTER = 4, REGISTER = 5) :
    GLOBAL (COMMON RABREG)
    NOPRESERVE (2,3,4,5,6) %;
```

```
L_CACHE =
    RL$CACHE =
    JSB (REGISTER = 1, REGISTER = 2, REGISTER = 3) :
    GLOBAL (COMMON IOREG)
    NOPRESERVE (1,2,3)
    NOTUSED (8,9,10,11) %;
```

```
L_CHECK_SEGMENT =
    RL$CHECK_SEGMENT =
    JSB (REGISTER = 0, REGISTER = 4, REGISTER = 2) :
    GLOBAL (R_IDX_DFN)
    NOPRESERVE (2,4,5)
    PRESERVE (1) %;
```

```
L_CHKSUM =
    RL$CHKSUM =
    JSB (REGISTER = 5) :
    NOPRESERVE (0,1,2) %;
```

```
L_COMPARE_KEY =
```

```
0554 0
0555 0
0556 0
0557 0
0558 0
0559 0
0560 0
0561 0
0562 0
0563 0
0564 0
0565 0
0566 0
0567 0
0568 0
0569 0
0570 0
0571 0
0572 0
M 0573 0
M 0574 0
M 0575 0
M 0576 0
M 0577 0
0578 0
0579 0
M 0580 0
M 0581 0
M 0582 0
0583 0
0584 0
M 0585 0
M 0586 0
M 0587 0
M 0588 0
0589 0
0590 0
M 0591 0
M 0592 0
M 0593 0
M 0594 0
M 0595 0
0596 0
0597 0
M 0598 0
M 0599 0
M 0600 0
M 0601 0
M 0602 0
0603 0
0604 0
M 0605 0
M 0606 0
M 0607 0
0608 0
0609 0
M 0610 0
```


C 2
15-Sep-1984 22:56:58
15-Sep-1984 22:56:57

VAX-11 Bliss-32 V4.0-742 Page 16
_\$255\$DUA28:[RMS.OBJ]RMSINTDEF.R32;1 (9)

0611 0
0612 0
0613 0
0614 0
0615 0
0616 0
0617 0
0618 0
0619 0
0620 0
0621 0
0622 0
0623 0
0624 0
0625 0
0626 0
0627 0
0628 0
0629 0
0630 0
0631 0
0632 0
0633 0
0634 0
0635 0
0636 0
0637 0
0638 0
0639 0
0640 0
0641 0
0642 0
0643 0
0644 0
0645 0
0646 0
0647 0
0648 0
0649 0
0650 0
0651 0
0652 0
0653 0
0654 0
0655 0
0656 0
0657 0
0658 0
0659 0
0660 0
0661 0
0662 0
0663 0
0664 0
0665 0
0666 0
0667 0

```
RL$COMPARE_KEY =  
JSB (REGISTER = 1, REGISTER = 3, REGISTER = 0) :  
GLOBAL (R_IDX_DFN)  
NOPRESERVE (3) %,  
  
L_ERROR_LINK1 =  
RL$ERROR_LINK1 =  
JSB () :  
GLOBAL (COMMON_RABREG)  
PRESERVE (0) %,  
  
L_ERROR_LINK2 =  
RL$ERROR_LINK2 =  
JSB () :  
GLOBAL (COMMON_RABREG, R_IDX_DFN)  
PRESERVE (0) %,  
  
L_EXTEND0 =  
RL$EXTEND0 =  
JSB (REGISTER = 5, REGISTER = 6; REGISTER = 1, REGISTER = 6) :  
GLOBAL (COMMON_FABREG)  
NOPRESERVE (2,3,4,5) %,  
  
L_FABREG =  
RL$FABREG =  
JSB () :  
GLOBAL (COMMON_FABREG)  
NOPRESERVE (0,1) %,  
  
L_FABREG_7 =  
RL$FABREG_7 =  
JSB () :  
GLOBAL (COMMON_FABREG, R_IDX_DFN) %,  
  
L_GETSPC =  
RL$GETSPC =  
JSB (REGISTER = 1, REGISTER = 2; REGISTER = 1) :  
GLOBAL (R_IMPURE)  
NOPRESERVE (2,3,4)  
NOTUSED (8,9,10) %,  
  
L_JSB =  
RL$JSB =  
JSB () %,  
  
L_JSB01 =  
RL$JSB01 =  
JSB (REGISTER = 0, REGISTER = 1) :  
GLOBAL (R_BKT_ADDR, R_REC_ADDR, R_IDX_DFN, R_IRAB, R_IFAB)  
NOPRESERVE (0,1) %,  
  
L_LINK_7_10_11 =  
RL$LINK_7_10_11 =  
JSB () :  
GLOBAL (R_IDX_DFN, R_IFAB, R_IMPURE)  
NOPRESERVE (0,1) %,
```


D 2
15-Sep-1984 22:56:58
15-Sep-1984 22:56:57

VAX-11 Bliss-32 V4.0-742
_S255\$DUA28:[RMS.OBJ]RMSINTDEF.R32;1 Page 17
(9)

.. M 0668 0
M 0669 0
M 0670 0
M 0671 0
0672 0
0673 0
M 0674 0
M 0675 0
M 0676 0
M 0677 0
0678 0
0679 0
M 0680 0
M 0681 0
M 0682 0
M 0683 0
0684 0
0685 0
M 0686 0
M 0687 0
M 0688 0
M 0689 0
0690 0
0691 0
M 0692 0
M 0693 0
M 0694 0
M 0695 0
0696 0
0697 0
M 0698 0
M 0699 0
M 0700 0
M 0701 0
0702 0
0703 0
M 0704 0
M 0705 0
M 0706 0
M 0707 0
0708 0
0709 0
M 0710 0
M 0711 0
M 0712 0
M 0713 0
0714 0
0715 0
M 0716 0
M 0717 0
M 0718 0
M 0719 0
0720 0
0721 0
M 0722 0
M 0723 0
M 0724 0

```
L_PRESERVE1 =
    RL$PRESERVE1 =
    JSB ( ) :
    GLOBAL (COMMON_RABREG, R_BDB, R_REC_ADDR, R_IDX_DFN)
    PRESERVE (1) %,

L_QUERY_AND_LOCK =
    RL$QUERY AND LOCK =
    JSB (REGISTER = 1, REGISTER = 2) :
    GLOBAL (COMMON_RABREG)
    NOPRESERVE (3) %,

L_RABREG =
    RL$RABREG =
    JSB ( ) :
    GLOBAL (COMMON_RABREG)
    NOPRESERVE (0,T) %,

L_RABREG_4 =
    RL$RABREG_4 =
    JSB ( ) :
    GLOBAL (COMMON_RABREG, R_BDB)
    NOPRESERVE (0,T) %,

L_RABREG_4567 =
    RL$RABREG_4567 =
    JSB ( ) :
    GLOBAL (COMMON_RABREG, COMMON_IOREG, R_REC_ADDR, R_IDX_DFN)
    NOPRESERVE (0,T) %,

L_RABREG_457 =
    RL$RABREG_457 =
    JSB ( ) :
    GLOBAL (COMMON_RABREG, COMMON_IOREG, R_IDX_DFN)
    NOPRESERVE (0,T) %,

L_RABREG_467 =
    RL$RABREG_467 =
    JSB ( ) :
    GLOBAL (COMMON_RABREG, R_BDB, R_REC_ADDR, R_IDX_DFN)
    NOPRESERVE (0,T) %,

L_RABREG_567 =
    RL$RABREG_567 =
    JSB ( ) :
    GLOBAL (COMMON_RABREG, R_BKT_ADDR, R_REC_ADDR, R_IDX_DFN)
    NOPRESERVE (0,T) %,

L_RABREG_67 =
    RL$RABREG_67 =
    JSB ( ) :
    GLOBAL (COMMON_RABREG, R_REC_ADDR, R_IDX_DFN)
    NOPRESERVE (0,T) %,

L_RABREG_7 =
    RL$RABREG_7 =
    JSB ( ) :
```

E 2
15-Sep-1984 22:56:58
15-Sep-1984 22:56:57

VAX-11 Bliss-32 V4.0-742
_S255SDUA28:[RMS.OBJ]RMSINTDEF.R32;1 Page 18
(9)

0725 0
0726 0
0727 0
0728 0
0729 0
0730 0
0731 0
0732 0
0733 0
0734 0
0735 0
0736 0
0737 0
0738 0
0739 0
0740 0
0741 0
0742 0
0743 0
0744 0
0745 0
0746 0
0747 0
0748 0
0749 0
0750 0
0751 0
0752 0
0753 0
0754 0
0755 0
0756 0
0757 0
0758 0
0759 0
0760 0
0761 0
0762 0
0763 0
0764 0
0765 0
0766 0
0767 0
0768 0
0769 0
0770 0
0771 0
0772 0
0773 0
0774 0
0775 0
0776 0
0777 0
0778 0
0779 0
0780 0
0781 0

GLOBAL (COMMON RABREG, R_IDX_DFN)
NOPRESERVE (0,T) %;

L_REC_OVHD =
RL\$REC_OVHD =
JSB (REGISTER = 1; REGISTER = 1) :
GLOBAL (R_REC_ADDR, R_IDX_DFN, R_IFAB) %;

L_RELEASE =
RL\$RELEASE =
JSB (REGISTER = 3) :
GLOBAL (R_BDB, R_IRAB, R_IFAB, R_IMPURE)
NOPRESERVE (1,2)
NOTUSED (8) %;

L_RELEASE_FAB =
RL\$RELEASE_FAB =
JSB (REGISTER = 3) :
GLOBAL (R_BDB, R_IFAB, R_IFAB_FILE, R_IMPURE)
NOPRESERVE (1,2)
NOTUSED(8) %;

L_RETSPC =
RL\$RETSPC =
JSB (REGISTER= 2, REGISTER = 3, REGISTER = 4) :
GLOBAL (R_IMPURE)
NOPRESERVE (2,3,5)
NOTUSED (8,9,10) %;

L_SIDR_FIRST =
RL\$SIDR_FIRST =
JSB (STANDARD; REGISTER = 1, REGISTER = 2) :
GLOBAL (R_REC_ADDR, R_IDX_DFN, COMMON_RABREG) %;

L_XSUMO =
RL\$XSUMO =
JSB () :
GLOBAL (COMMON_FABREG)
NOPRESERVE (0,T,4) %;

```
*****
*
* Copyright (c) 1982, 1983
* by DIGITAL Equipment Corporation, Maynard, Mass.
*
* This software is furnished under a license and may be used and copied
* only in accordance with the terms of such license and with the
* inclusion of the above copyright notice. This software or any other
* copies thereof may not be provided or otherwise made available to any
* other person. No title to and ownership of the software is hereby
* transferred.
*
* The information in this software is subject to change without notice
* and should not be construed as a commitment by DIGITAL Equipment
* Corporation.
*
```



```

0782 0  ! * DIGITAL assumes no responsibility for the use or reliability of its *
0783 0  ! * software on equipment which is not supplied by DIGITAL. *
0784 0  ! *
0785 0  ! *****
0786 0  ! *****
0787 0  ! Created 15-SEP-1984 22:54:35 by VAX-11 SDL V2.0 Source: 15-SEP-1984 22:49:24 _$255$DUA28:[RMS.SRC]RMSINTS
0788 0  ! *****
0789 0
0790 0
0791 0  ! *** MODULE $IFBDEF ***
0792 0
0793 0  ! NOTE: The fields thru JNLBDB inclusive are common between the ifb and irb
0794 0
0795 0  ! literal IFBSC_BID = 11; ! ifab id code
0796 0  ! literal IFBSM_PUT = 1;
0797 0  ! literal IFBSM_GET = 2;
0798 0  ! literal IFBSM_DEL = 4;
0799 0  ! literal IFBSM_UPD = 8;
0800 0  ! literal IFBSM_TRN = 16;
0801 0  ! literal IFBSM_BIO = 32;
0802 0  ! literal IFBSM_BRO = 64;
0803 0  ! literal IFBSM_EXE = 128;
0804 0  ! literal IFBSC_SEQ = 0; ! sequential
0805 0  ! literal IFBSC_REL = 1; ! relative
0806 0  ! literal IFBSC_IDX = 2; ! indexed
0807 0  ! literal IFBSC_DIR = 3; ! direct
0808 0  ! literal IFBSC_MAXORG = 2; ! release 1.5 maximum
0809 0  ! literal IFBSK_FHAEND = 102; ! end of file header attributes
0810 0  ! literal IFBSC_FHAEND = 102; ! end of file header attributes
0811 0  ! literal IFBSC_KBUFNUM = 6; ! constant - the number of key buffers allocated
0812 0  ! literal IFBSM_ONLY_RU = 1;
0813 0  ! literal IFBSM_RU = 2;
0814 0  ! literal IFBSM_BI = 4;
0815 0  ! literal IFBSM_AI = 8;
0816 0  ! literal IFBSM_AT = 16;
0817 0  ! literal IFBSM_NEVER_RU = 32;
0818 0  ! literal IFBSM_RU_RECVR = 1;
0819 0  ! literal IFBSM_AI_RECVR = 2;
0820 0  ! literal IFBSM_BI_RECVR = 4;
0821 0  ! literal IFBSM_VALID_AT = 1;
0822 0  ! literal IFBSM_JNL = 2;
0823 0  ! literal IFBSM_RUP = 4;
0824 0  ! literal IFBSM_RU_RLK = 8;
0825 0  ! literal IFBSM_DONE_ASS_JNL = 16;
0826 0  ! literal IFBSK_BLN_SEQ = 172;
0827 0  ! literal IFBSC_BLN_SEQ = 172;
0828 0  ! --
0829 0
0830 0  ! organization-dependent fields
0831 0
0832 0  ! the following fields are used differently
0833 0  ! depending upon the file's organization
0834 0
0835 0  ! ++
0836 0
0837 0  ! relative org specific fields
0838 0

```



```

0839 0 literal IFB$$ IFBDEF = 172;
0840 0 (but have definitions that allow them to
0841 0 be referenced from the start of the ifab)
0842 0 ++
0843 0 the following bits are defined in
0844 0 common with the irab
0845 0
0846 0 macro IFBSV_BUSY = 4,0,1,0 %; | stream busy
0847 0 macro IFBSV_EOF = 4,1,1,0 %; | file positioned at eof
0848 0 macro IFBSV_PPF_IMAGE = 4,2,1,0 %; | flag for indirect processing of process-
0849 0 ! permanent files (restricts allowable operations)
0850 0 macro IFBSV_ASYNC = 4,3,1,0 %; | async i/o flag (must be zero for ifab)
0851 0 macro IFBSV_ASYNCWAIT = 4,4,1,0 %; | wait on async i/o (must be zero for ifab)
0852 0 --
0853 0
0854 0 ifab specific bits
0855 0
0856 0 macro IFBSV_ACCESSED = 4,5,1,0 %; | file is accessed
0857 0 macro IFBSV_ANSI_D = 4,6,1,0 %; | ansi d variable records
0858 0 macro IFBSV_RWC = 4,7,1,0 %; | copy of fop bit from open
0859 0 macro IFBSV_DMO = 4,8,1,0 %; | copy of fop bit from open
0860 0 macro IFBSV_SPL = 4,9,1,0 %; | copy of fop bit from open
0861 0 macro IFBSV_SCF = 4,10,1,0 %; | copy of fop bit from open
0862 0 macro IFBSV_DLT = 4,11,1,0 %; | copy of fop bit from open
0863 0 macro IFBSV_DFW = 4,12,1,0 %; | deferred write (copy of fop bit from $open)
0864 0 macro IFBSV_SQO = 4,13,1,0 %; | sequential operations only
0865 0 macro IFBSV_PPF_INPUT = 4,14,1,0 %; | this is command 'input' stream
0866 0 macro IFBSV_NFS = 4,15,1,0 %; | non-file structured flag
0867 0 macro IFBSV_WRTACC = 4,16,1,0 %; | logical or of fac bits:
0868 0 ! put, upd, del, trn
0869 0 macro IFBSV_MSE = 4,17,1,0 %; | multi-streams enabled
0870 0 macro IFBSV_CREATE = 4,18,1,0 %; | set if doing create (may be "create if")
0871 0 macro IFBSV_NORECLK = 4,19,1,0 %; | record locking not required
0872 0 ! (i.e., no shared access or multi-stream)
0873 0 macro IFBSV_RW_ATTR = 4,20,1,0 %; | set if file attributes must be re-written
0874 0 macro IFBSV_TMP = 4,21,1,0 %; | temporary file (i.e., no directory entry)
0875 0 macro IFBSV_TEF = 4,22,1,0 %; | truncate at eof due to large auto extend
0876 0 macro IFBSV_STALL_LOCK = 4,23,1,0 %; | RMS is stalled for file lock
0877 0 macro IFBSV_SEQFIC = 4,24,1,0 %; | this is really a sequential file being shared
0878 0 macro IFBSV_SEARCH = 4,25,1,0 %; | search ifab - left during wildcard operations
0879 0 macro IFBSV_RMS_STALL = 4,26,1,0 %; | RMS is stalled on this file operation
0880 0 macro IFBSV_RESTART = 4,27,1,0 %; | Reopen or recreate operation in progress
0881 0 macro IFBSV_FILEFOUND = 4,28,1,0 %; | A file was found on a search operation
0882 0 macro IFBSV_DAP_OPEN = 4,29,1,0 %; | open/create function was performed via dap
0883 0 macro IFBSV_DAP = 4,30,1,0 %; | data access protocol transmission
0884 0 macro IFBSV_NSP = 4,31,1,0 %; | network services protocol transmission
0885 0 macro IFBSL_PRIM_DEV = 0,0,32,0 %; | device characteristics bits
0886 0 ! (for primary device - bit encoding same as for fab)
0887 0 macro IFBSL_BKPBITS = 4,0,32,0 %; | bookkeeping bits
0888 0 !
0889 0 macro IFBSB_BID = 8,0,8,0 %; | block id
0890 0 macro IFBSB_BLN = 9,0,8,0 %; | block length in longwords
0891 0 macro IFBSB_MODE = 10,0,8,0 %; | caller's mode
0892 0 macro IFBSB_EFN = 11,0,8,0 %; | event flag used for synchronous qio
0893 0 macro IFBSL_IOS = 12,0,32,0 %; | internal i/o status block
0894 0 macro IFBSL_BWB = 12,0,32,0 %; | bucket wait block for inter stream waiting
0895 0 macro IFBSW_IOS2 = 14,0,16,0 %; | high word of io status block

```



```

0896 0 macro IFBSL_IOS4 = 16,0,32,0 %;
0897 0 macro IFBSL_ASBADDR = 20,0,32,0 %;
0898 0 macro IFBSL_ARGLST = 24,0,32,0 %;
0899 0 macro IFBSL_IRAB_LNK = 28,0,32,0 %;
0900 0 macro IFBSW_CHNL = 32,0,16,0 %;
0901 0 macro IFBSB_FAC = 34,0,8,0 %;
0902 0 macro IFBSV_PUT = 34,0,1,0 %;
0903 0 macro IFBSV_GET = 34,1,1,0 %;
0904 0 macro IFBSV_DEL = 34,2,1,0 %;
0905 0 macro IFBSV_UPD = 34,3,1,0 %;
0906 0 macro IFBSV_TRN = 34,4,1,0 %;
0907 0 macro IFBSV_BIO = 34,5,1,0 %;
0908 0 macro IFBSV_BRO = 34,6,1,0 %;
0909 0 macro IFBSV_EXE = 34,7,1,0 %;
0910 0 note: if both bio and bro set, implies block i/o
0911 0 access only allowed for this connect, resets
0912 0 to bro on disconnect (seq. file org. only).
0913 0
0914 0 macro IFBSB_ORGCASE = 35,0,8,0 %;
0915 0 macro IFBSL_LAST_FAB = 36,0,32,0 %;
0916 0 macro IFBSW_IFI = 40,0,16,0 %;
0917 0 macro IFBSW_ECHO_ISI = 42,0,16,0 %;
0918 0 macro IFBSL_ATJN[BUF = 44,0,32,0 %;
0919 0 macro IFBSL_JNLBDB = 48,0,32,0 %;
0920 0 ! -----*****
0921 0 macro IFBSL_EXTJNLBUF = 52,0,32,0 %;
0922 0 macro IFBSL_FWA_PTR = 56,0,32,0 %;
0923 0 macro IFBSL_NWA_PTR = 60,0,32,0 %;
0924 0 macro IFBSL_BDB_FLNK = 64,0,32,0 %;
0925 0 macro IFBSL_BDB_BLNK = 68,0,32,0 %;
0926 0 macro IFBSL_DEVBUSIZ = 72,0,32,0 %;
0927 0 macro IFBSW_RTDEQ = 76,0,16,0 %;
0928 0 macro IFBSB_SHR = 78,0,8,0 %;
0929 0 macro IFBSB_AGENT_MODE = 79,0,8,0 %;
0930 0
0931 0 ! +++++*****
0932 0
0933 0 the following fields must remain as is since
0934 0 they correspond to the rms attributes stored
0935 0 in the file header
0936 0
0937 0 macro IFBSB_RFMORG = 80,0,8,0 %;
0938 0 macro IFBSV_RFM = 80,0,4,0 %;
0939 0 literal IFBS$ RFM = 4;
0940 0 macro IFBSV_ORG = 80,4,4,0 %;
0941 0 literal IFBS$ ORG = 4;
0942 0 macro IFBSB_RAT = 81,0,8,0 %;
0943 0 macro IFBSW_LRL = 82,0,16,0 %;
0944 0 macro IFBSL_HBK_DISK = 84,0,32,0 %;
0945 0 macro IFBSL_EBK_DISK = 88,0,32,0 %;
0946 0 macro IFBSW_FFB = 92,0,16,0 %;
0947 0 macro IFBSB_BKS = 94,0,8,0 %;
0948 0 macro IFBSB_FSZ = 95,0,8,0 %;
0949 0 macro IFBSW_MRS = 96,0,16,0 %;
0950 0 macro IFBSW_DEQ = 98,0,16,0 %;
0951 0 macro IFBSW_GBC = 100,0,16,0 %;
0952 0 ! -----*****

```

2nd longword of io status block
address of asynchronous context block
user call parameters addr
pointer to irab(s)
i/o channel number
file access
(same as in fab's fac field)

copy of org for case dispatching
address of fab for last operation
Internal file Identifier, the one we gave to the user
ISI of stream to echo records from SYSSINPUT
address of IFAB audit trail buffer
address of Journaling BDB for FAB operations

pointer to buffer to contain extend journal record
pointer to file work area control block
pointer to network work area control block
pointer to bdb(s)
bdb backward link
device default (or bls if mt) buff size
run-time default extend quantity
File sharing bits from users FAB
User's FABSV_FILE_MODE field, maximized with mode of caller

organization and record format
record format (n.b. constant values defined in rfm field of fab)
file organization
record attributes (n.b. bit offsets defined in rat field of fab)
longest record's length (or fixed record length)
hi vbn allocated (note: disk format!)
eof vbn (note: disk format!)
first free byte in eof block
bucket size (! vbns)
record header size for vfc
max record size allowable
default extend quantity
global buffer count


```

0953 0 macro IFB$B_DRT_REHIT = 104,0,8,0 %;
0954 0 macro IFB$B_GBL_REHIT = 105,0,8,0 %;
0955 0 macro IFB$B_RNS_LEN = 108,0,32,0 %;
0956 0 macro IFB$B_LOCK_BDB = 108,0,32,0 %;
0957 0 macro IFB$B_HBK = 112,0,32,0 %;
0958 0 macro IFB$B_EBK = 116,0,32,0 %;
0959 0 macro IFB$B_SFSB_PTR = 120,0,32,0 %;
0960 0 macro IFB$B_GBSB_PTR = 124,0,32,0 %;
0961 0 macro IFB$B_PAR_LOCK_ID = 128,0,32,0 %;
0962 0 macro IFB$W_AVLCL = 132,0,16,0 %;
0963 0 macro IFB$W_AVGBPB = 134,0,16,0 %;
0964 0 macro IFB$B_GBH_PTR = 136,0,32,0 %;
0965 0 macro IFB$B_AS_DEV = 140,0,32,0 %;
0966 0 ! AS DEV and ASDEVBSIZ *)
0967 0 macro IFB$B_ASDEVBSIZ = 148,0,32,0 %;
0968 0 macro IFB$B_BLBFLNK = 152,0,32,0 %;
0969 0 macro IFB$B_BLBBLNK = 156,0,32,0 %;
0970 0 macro IFB$B_JNLFLG = 160,0,8,0 %;
0971 0 macro IFB$V_ONLY_RU = 160,0,1,0 %;
0972 0 macro IFB$V_RU = 160,1,1,0 %;
0973 0 macro IFB$V_BI = 160,2,1,0 %;
0974 0 macro IFB$V_AI = 160,3,1,0 %;
0975 0 macro IFB$V_AT = 160,4,1,0 %;
0976 0 macro IFB$V_NEVER_RU = 160,5,1,0 %;
0977 0 macro IFB$B_RECVRFLGS = 161,0,8,0 %;
0978 0 macro IFB$V_RU_RECVR = 161,0,1,0 %;
0979 0 macro IFB$V_AI_RECVR = 161,1,1,0 %;
0980 0 macro IFB$V_BI_RECVR = 161,2,1,0 %;
0981 0 macro IFB$B_JNCLFLG2 = 162,0,8,0 %;
0982 0 macro IFB$V_VALID_AT = 162,0,1,0 %;
0983 0 macro IFB$V_JNL = 162,1,1,0 %;
0984 0 macro IFB$V_RUP = 162,2,1,0 %;
0985 0 macro IFB$V_RU_RLK = 162,3,1,0 %;
0986 0 macro IFB$V_DONE_ASS_JNL = 162,4,1,0 %;
0987 0 macro IFB$B_RJB = 164,0,32,0 %;
0988 0 macro IFB$W_BUFFER_OFFSET = 168,0,16,0 %;
0989 0 literal IFB$K_BLN_REL = 180;
0990 0 literal IFB$C_BLN_REL = 180;
0991 0 --
0992 0 ++
0993 0
0994 0 indexed org specific fields
0995 0
0996 0 literal IFB$S_IFBDEF1 = 180;
0997 0 macro IFB$B_MRN = 172,0,32,0 %;
0998 0 macro IFB$B_DVBN = 176,0,32,0 %;
0999 0 literal IFB$K_BLN_IDX = 184;
1000 0 literal IFB$C_BLN_IDX = 184;
1001 0 literal IFB$K_BLN = 184;
1002 0 literal IFB$C_BLN = 184;
1003 0 --
1004 0 literal IFB$S_IFBDEF2 = 184;
1005 0 macro IFB$B_IDX_PTR = 172,0,32,0 %;
1006 0 macro IFB$B_AVBN = 176,0,8,0 %;
1007 0 macro IFB$B_AMAX = 177,0,8,0 %;
1008 0 macro IFB$B_NUM_KEYS = 178,0,8,0 %;
1009 0 macro IFB$B_UBUFSZ = 179,0,8,0 %;

```

```

hit count for local dirty buffers.
rehit count for gbl buffers.
resultant name string length (used as a temp field by $search)
lock bdb address (used by $extend for rel. file)
hi vbn allocated.
eof vbn.
pointer to shared file synchronization block
pointer to global buffer synchronization block.
Parent lock ID for bucket locks (get from SFSB.)
local buffers available.
gbl ptr blocks available.
pointer to global header.
assigned device characteristics
assigned device buffer size
Forward link to BLB chain.
Back link to BLB chain.
journaling attribute flags
Recovery Unit journaling, no access outside RU
Recovery Unit journaling
Before Image journaling
After Image journaling
Audit Trail journaling
never do RU journaling
Recovery flags
Recovery Unit Rollback in progress
AI Roll Forward Recovery in progress
BI Roll Backward Recovery in progress
Secondary journaling flags (generally operation specific)
AT entry in IFB buffer is valid and should be written
Journaling Initialized for this file
Recovery Unit in progress
Fake record locking during recovery unit
Journal channels already assigned
RMS Journaling Block address
! ANSI buffer offset
(rel) max record number
(rel) first data bucket vbn
ifab length
ifab length
(idx) pointer to primary key index descriptor
(idx) vbn of 1st area descriptor
(idx) total number of area descriptors
(idx) ! of keys in file
(idx) update buffer size for keys

```



```

1010 0 macro IFBSW_KBUFSZ = 180,0,16,0 %;      ! (idx) key buffer size
1011 0 macro IFBSB_EXTRABUF = 182,0,8,0 %;      ! (idx) number of extra buffers for 'cache'ing
1012 0 macro IFBSB_PLG_VER = 183,0,8,0 %;      ! (idx) prologue version number
1013 0
1014 0 *** MODULE $IRBDEF ***
1015 0
1016 0     IRB field definitions
1017 0
1018 0     Internal rab (irb)
1019 0
1020 0     There is 1 irab per connected record access stream
1021 0
1022 0
1023 0     NOTE: The fields thru JNLBDB inclusive are common between the irb and ifb
1024 0
1025 0 literal IRB$C_BID = 10;                      ! irab code
1026 0 literal IRB$M_POSINSERT = 1;
1027 0 literal IRB$M_SRCHGT = 2;
1028 0 literal IRB$M_POSDELETE = 4;
1029 0 literal IRB$M_NEW_IDX = 8;
1030 0 literal IRB$M_SRCHGE = 16;
1031 0 literal IRB$M_NORLS_RNF = 32;
1032 0 literal IRB$M_FIRST_TIM = 64;
1033 0 literal IRB$M_PRM = 128;
1034 0 literal IRB$M_DUP_KEY = 256;
1035 0 literal IRB$M_DEL_SEEN = 512;
1036 0 literal IRB$M_LAST_GT = 1024;
1037 0 literal IRB$M_BKT_NO_LO = 1;
1038 0 literal IRB$M_NEW_BKTS = 6;
1039 0 literal IRB$M_REC_W_LO = 8;
1040 0 literal IRB$M_CONT_BKT = 16;
1041 0 literal IRB$M_CONT_R = 32;
1042 0 literal IRB$M_EMPTY_BKT = 64;
1043 0 literal IRB$M_DUPS_SEEN = 128;
1044 0 literal IRB$M_BKT_NO = 3;
1045 0 literal IRB$M_BIG_SPLIT = 4;
1046 0 literal IRB$M_SPL_IDX = 1;
1047 0 literal IRB$M_EMPTY_SEEN = 2;
1048 0 literal IRB$M_VALID_AT = 1;
1049 0 literal IRB$K_BLN_REL = 100;
1050 0 literal IRB$C_BLN_REL = 100;
1051 0 ++
1052 0
1053 0     sequential org specific fields
1054 0
1055 0 literal IRB$K_BLN_SEQ = 108;
1056 0 literal IRB$C_BLN_SEQ = 108;
1057 0 literal IRB$S_IRBDEF = 108;
1058 0     to apply from start of irab
1059 0 ++
1060 0
1061 0     the following bits are defined in common
1062 0     with the ifab
1063 0
1064 0 macro IRB$V_BUSY = 4,0,1,0 %;      ! file busy
1065 0 macro IRB$V_EOF = 4,1,1,0 %;      ! stream positioned at eof
1066 0 macro IRB$V_PPF_IMAGE = 4,2,1,0 %; ! flag for indirect processing of process-

```



```

1067 0 ! permanent file
1068 0 macro IRBSV_ASYNC = 4,3,1,0 %; ! asynchronous i/o request
1069 0 macro IRBSV_ASYNCWAIT = 4,4,1,0 %; ! $wait issued for asynchronous i/o request
1070 0 --
1071 0
1072 0 ! irab specific bits
1073 0
1074 0 macro IRBSV_FIND_LAST = 4,5,1,0 %; ! last operation was a find
1075 0 macro IRBSV_PUTS_LAST = 4,6,1,0 %; ! last operation was a put sequential
1076 0 macro IRBSV_BIO_LAST = 4,7,1,0 %; ! this/last operation is/was a block i/o operation
1077 0 ! note: this bit is set only if mixed block and record
1078 0 ! operations (bro access). after call to rmsrset
1079 0 ! refers to the current operation and bro_sw gives
1080 0 ! type of last operation.
1081 0 macro IRBSV_BRO_SW = 4,8,1,0 %; ! switched from record operation to block i/o operation
1082 0 macro IRBSV_FIND = 4,9,1,0 %; ! operation is a find
1083 0 macro IRBSV_RAHWBH = 4,10,1,0 %; ! read ahead or write behind processing
1084 0 macro IRBSV_SKIP_NEXT = 4,11,1,0 %; ! skip to next record flag for index fo
1085 0 macro IRBSV_DUP = 4,12,1,0 %; ! duplicate records seen
1086 0 macro IRBSV_UNLOCK_RP = 4,13,1,0 %; ! release lock on current (rp) record
1087 0 macro IRBSV_PPF_EOF = 4,14,1,0 %; ! give one-shot rms_eof error on sys$input
1088 0 macro IRBSV_PPF_SKIP = 4,15,1,0 %; ! skip sys$input record ($deck), redoing $get
1089 0 ! or $find on next record
1090 0 macro IRBSV_PPF_FNDV = 4,16,1,0 %; ! save value for find bit when ppf_skip set
1091 0 macro IRBSV_IDX_ERR = 4,17,1,0 %; ! index update error occurred
1092 0 macro IRBSV_RRV_ERR = 4,18,1,0 %; ! rrv update error occurred
1093 0 macro IRBSV_UPDATE = 4,19,1,0 %; ! operation is an update (indexed)
1094 0 macro IRBSV_UPDATE_IF = 4,20,1,0 %; ! operation was a $PUT -> $UPDATE
1095 0 macro IRBSV_ABOVELOCKD = 4,21,1,0 %; ! level above was locked by search_tree
1096 0 macro IRBSV_GBLBUFF = 4,22,1,0 %; ! global buffers are in use.
1097 0 macro IRBSV_CON_EOF = 4,23,1,0 %; ! file positioned at EOF by $CONNECT (isam)
1098 0 macro IRBSV_NO_WAIT = 4,24,1,0 %; ! do not wait for enqueues on query locks
1099 0 macro IRBSV_PPF_ECHO = 4,25,1,0 %; ! echo SYS$INPUT records to SYS$OUTPUT
1100 0 macro IRBSV_RMS_STALL = 4,26,1,0 %; ! RMS is stalled on this record operation
1101 0 macro IRBSV_RESTART = 4,27,1,0 %; ! Reconnect operation in progress
1102 0 macro IRBSV_DAP_CONN = 4,28,1,0 %; ! connect function was performed via dap
1103 0 macro IRBSV_RU_DELETE = 4,29,1,0 %; ! recovery unit deletion in progress
1104 0 macro IRBSV_RU_UNDEL = 4,30,1,0 %; ! recovery unit un-deletion in progress
1105 0 macro IRBSV_RU_UPDATE = 4,31,1,0 %; ! place new record is special RU UPDATE format
1106 0
1107 0 ! the following are alternate definitions for alternate
1108 0 ! (non-conflicting) use of the above bits
1109 0
1110 0 macro IRBSV_WRITE = 4,9,1,0 %; ! operation is a write
1111 0 macro IRBSL_IFAB_LNK = 0,0,32,0 %; ! pointer to ifab
1112 0 macro IRBSL_BKPBITS = 4,0,32,0 %; ! bookkeeping status bits
1113 0 !
1114 0 macro IRBSB_BID = 8,0,8,0 %; ! block id
1115 0 macro IRBSB_BLN = 9,0,8,0 %; ! block length in longwords
1116 0 macro IRBSB_MODE = 10,0,8,0 %; ! caller's mode
1117 0 macro IRBSB_EFN = 11,0,8,0 %; ! event flag for synchronous io
1118 0 macro IRBSL_IOS = 12,0,32,0 %; ! internal i/o status block
1119 0 macro IRBSL_BWB = 12,0,32,0 %; ! bucket wait block for inter stream locking
1120 0 macro IRBSW_IOS2 = 14,0,16,0 %; ! high word of io status block
1121 0 macro IRBSL_IOS4 = 16,0,32,0 %; ! io status block (2nd longword)
1122 0 macro IRBSL_ASBADDR = 20,0,32,0 %; ! address of permanent asynchronous context block
1123 0 macro IRBSL_ARGLIST = 24,0,32,0 %; ! user arg list address

```



```

1124 0 ! if async, points to copy at head
1125 0 ! of async context block
1126 0 macro IRBSL_IRAB_LNK = 28,0,32,0 %;
1127 0 macro IRBSL_CURBDB = 32,0,32,0 %;
1128 0 macro IRBSL_LAST_RAB = 36,0,32,0 %;
1129 0 macro IRBSW_ISI = 40,0,16,0 %;
1130 0 macro IRBSL_ATJNLBUF = 44,0,32,0 %;
1131 0 macro IRBSL_JNLBDB = 48,0,32,0 %;
1132 0 ! -----*****
1133 0 macro IRBSL_IDENT = 52,0,32,0 %;
1134 0 macro IRBSL_RLB_LNK = 56,0,32,0 %;
1135 0 macro IRBSL_NXTBDB = 60,0,32,0 %;
1136 0 macro IRBSL_NRP = 64,0,32,0 %;
1137 0 macro IRBSL_NRP_VBN = 64,0,32,0 %;
1138 0 macro IRBSB_CACHREFLGS = 64,0,8,0 %;
1139 0 macro IRBSB_STOPLEVEL = 65,0,8,0 %;
1140 0 macro IRBSW_SRCHFLAGS = 66,0,16,0 %;
1141 0 macro IRBSV_POSINSERT = 66,0,1,0 %;
1142 0 macro IRBSV_SRCHGT = 66,1,1,0 %;
1143 0 macro IRBSV_POSDELETE = 66,2,1,0 %;
1144 0 macro IRBSV_NEW_IDX = 66,3,1,0 %;
1145 0 macro IRBSV_SRCRGE = 66,4,1,0 %;
1146 0 macro IRBSV_NORLS_RNF = 66,5,1,0 %;
1147 0 macro IRBSV_FIRST_TIM = 66,6,1,0 %;
1148 0 macro IRBSV_PRM = 66,7,1,0 %;
1149 0 macro IRBSV_DUP_KEY = 66,8,1,0 %;
1150 0 macro IRBSV_DEL_SEEN = 66,9,1,0 %;
1151 0 macro IRBSV_LAST_GT = 66,10,1,0 %;
1152 0 ! and a next record during a $GET/$FIND
1153 0 ! should be set
1154 0 macro IRBSL_NRP_OFF = 68,0,32,0 %;
1155 0 macro IRBSL_CURVBN = 68,0,32,0 %;
1156 0 macro IRBSW_NRP_OFF = 68,0,16,0 %;
1157 0 macro IRBSB_SPL_BITS = 68,0,8,0 %;
1158 0 macro IRBSV_BKT_NO_LO = 68,0,1,0 %;
1159 0 macro IRBSV_NEW_BKTS = 68,1,2,0 %;
1160 0 literal IRBS$ NEW_BKTS = 2;
1161 0 macro IRBSV_REC_W_LO = 68,3,1,0 %;
1162 0 macro IRBSV_CONT_BKT = 68,4,1,0 %;
1163 0 macro IRBSV_CONT_R = 68,5,1,0 %;
1164 0 macro IRBSV_EMPTY_BKT = 68,6,1,0 %;
1165 0 macro IRBSV_DUPS_SEEN = 68,7,1,0 %;
1166 0 macro IRBSV_BKT_NO = 68,0,2,0 %;
1167 0 literal IRBS$ BKT_NO = 2;
1168 0 macro IRBSV_BIG_SPLIT = 68,2,1,0 %;
1169 0 macro IRBSV_SPL_IDX = 68,0,1,0 %;
1170 0 macro IRBSV_EMPTY_SEEN = 68,1,1,0 %;
1171 0 macro IRBSL_RP = 72,0,32,0 %;
1172 0 macro IRBSL_RP_VBN = 72,0,32,0 %;
1173 0 macro IRBSW_POS_INS = 72,0,16,0 %;
1174 0 macro IRBSW_SPLIT = 74,0,16,0 %;
1175 0 macro IRBSL_RP_OFF = 76,0,32,0 %;
1176 0 macro IRBSL_LST_REC = 76,0,32,0 %;
1177 0 macro IRBSL_PTR_VBN = 76,0,32,0 %;
1178 0 macro IRBSW_RP_OFF = 76,0,16,0 %;
1179 0 macro IRBSW_SPLIT_1 = 76,0,16,0 %;
1180 0 macro IRBSW_SPLIT_2 = 78,0,16,0 %;

```

pointer to next irab
current bdb address
address of rab for last operation
Internal stream Identifier, the one we gave to the user
address of IRAB audit trail journaling buffer
address of journaling BDB for RAB operations

process unique identifier for the IRB
pointer to RLBs
next bdb address
next record pointer (relative record number)
next record pointer (relative)
cacheflags for calls to getbkt, cache, etc. (indexed)
level to stop at on tree search (indexed)
search flags (indexed)
position for insert
approximate search gt
position for delete
need to read in new idx dsc from file
approximate search ge
don't release bkt on rnf error, if set
flag to indicate 1st time for seq. processing
flag to indicate that the permanence bit in the bdb
a duplicate key seen on scan of any data bucket
a deleted record has been encountered between current
result of last search of compressed key bucket was GT

next record pointer offset (relative)
ybn of current record (relative)
bits for splitting (indexed)
low bit of bucket number processing
number of new buckets (0-3)
if splitting at pos_insert than rec goes w/ lo
middle bucket is a continuation bkt
right bucket is a continuation bkt
bucket contains no data records
dups seen on scan of bucket, any key

split up new index record and swing pointer
empty bucket passed over on posinsert
record pointer (relative record !)
record pointer (relative)
offset for position for insert for put (indexed)
first split point (indexed)
record pointer offset
last record address (indexed)
pointer vbn used by find_by_rrv (indexed)
record pointer offset
second split point -- 3-bkt split (indexed)
third split point -- 4-bkt split (indexed)


```

1181 0 macro IRBSL_OWNER_ID = 80,0,32,0 %;      ! owner id used for record locks
1182 0 macro IRBSW_OWN_ID = 80,0,16,0 %;         ! index part of process id (pid)
1183 0 macro IRBSW_OWN_ISI = 82,0,16,0 %;        ! isi value for this irab
1184 0 macro IRBSB_PPF_ISI = 82,0,8,0 %;         ! isi value for this process-permanent irab
1185 0 macro IRBSB_BCNT = 84,0,8,0 %;            ! i/o buffer count
1186 0 macro IRBSB_MBC = 85,0,8,0 %;            ! multi-block count
1187 0 macro IRBSW_RSZ = 86,0,16,0 %;           ! record size from user
1188 0 macro IRBSL_RBF = 88,0,32,0 %;            ! user record buffer address
1189 0 macro IRBSB_MBF = 92,0,8,0 %;            ! Multi-buffer count from user's RAB
1190 0 macro IRBSB_JNLFLG3 = 93,0,8,0 %;        ! IRB journaling flags
1191 0 macro IRBSV_VALID_AT = 93,0,1,0 %;        ! IRB MJB contains valid AT entry to write
1192 0 ++
1193 0
1194 0      start of organization dependent fields
1195 0
1196 0 ++
1197 0
1198 0      used by sequential and relative files
1199 0
1200 0 macro IRBSW_CSIZ = 98,0,16,0 %;           ! current record size (seq)
1201 0 ++
1202 0
1203 0      relative org specific fields
1204 0
1205 0 macro IRBSL_TEMPO = 100,0,32,0 %;
1206 0 macro IRBSW_ROVHDSZ = 100,0,16,0 %;       ! overhead size for record
1207 0 macro IRBSB_PRE_CCTL = 100,0,8,0 %;       ! 'pre' carriage control
1208 0 macro IRBSB_POST_CCTL = 101,0,8,0 %;      ! 'post' carriage control
1209 0 macro IRBSW_RTOTCSZ = 102,0,16,0 %;       ! total size for record
1210 0 macro IRBSL_TEMP1 = 104,0,32,0 %;
1211 0 macro IRBSB_NVBNBNS = 104,0,8,0 %;        ! number of vbns transferred (nxtblk1)
1212 0
1213 0      indexed org specific fields
1214 0
1215 0 literal IRBSK_BLN_IDX = 196;
1216 0 literal IRBSC_BLN_IDX = 196;
1217 0 literal IRBSS_IRBDEF1 = 196;
1218 0 macro IRBSL_KEYBUF = 96,0,32,0 %;          ! address of internal key buffer & update buffer
1219 0 macro IRBSL_UPDBUF = 100,0,32,0 %;        ! address of internal update buffer
1220 0 macro IRBSL_RECBUF = 104,0,32,0 %;        ! address of internal record buffer
1221 0 macro IRBSL_OLDDBUF = 108,0,32,0 %;       ! address of internal old record buffer (updates only)
1222 0 macro IRBSL_RFA_VBN = 112,0,32,0 %;       ! save record vbn for nrp data
1223 0 macro IRBSL_UPD_BDB = 112,0,32,0 %;       ! save current bdb during insert operation
1224 0 macro IRBSL_LAST_VBN = 112,0,32,0 %;      ! last vbn at data level for update
1225 0 macro IRBSW_RFA_ID = 116,0,16,0 %;         ! save record id for search data
1226 0 macro IRBSW_LAST_ID = 116,0,16,0 %;       ! id for udr during update (plg 3)
1227 0 macro IRBSW_SAVE_POS = 118,0,16,0 %;       ! save duplicate position for nrp data
1228 0 macro IRBSL_NEXT_VBN = 120,0,32,0 %;       ! save next user data record VBN for nrp data
1229 0 macro IRBSL_PUTUP_VBN = 120,0,32,0 %;      ! RFA VBN of $PUT/$UPDATE record
1230 0 macro IRBSL_FIRST_VBN = 124,0,32,0 %;     ! save SISR first element VBN for search NRP data
1231 0 macro IRBSW_NEXT_ID = 128,0,16,0 %;       ! save next user data record ID for nrp data
1232 0 macro IRBSW_PUTUP_ID = 128,0,16,0 %;       ! ID of $PUT/$UPDATE record
1233 0 macro IRBSW_FIRST_ID = 130,0,16,0 %;       ! save SISR first element ID for search NRP data
1234 0 macro IRBSL_LOCK_BDB = 132,0,32,0 %;       ! lock bdb addr of level below on splits
1235 0 macro IRBSL_VBN_LEFT = 136,0,32,0 %;      ! left vbn of split
1236 0 macro IRBSL_MIDX_TMP1 = 136,0,32,0 %;      ! temporary one for make index
1237 0 macro IRBSL_VBN_RIGHT = 140,0,32,0 %;     ! right vbn of split

```



```

1238 0 macro IRB$L_MIDX_TMP2 = 140,0,32,0 %;
1239 0 macro IRB$L_VBN_MID = 144,0,32,0 %;
1240 0 macro IRB$L_MIDX_TMP3 = 144,0,32,0 %;
1241 0 macro IRB$L_NEXT_DOWN = 144,0,32,0 %;
1242 0 macro IRB$L_REC_COUNT = 148,0,32,0 %;
1243 0 macro IRB$L_LST_NCMP = 152,0,32,0 %;
1244 0 macro IRB$L_SPL_COUNT = 156,0,32,0 %;
1245 0 ! when splitting indexes and SIDs
1246 0 macro IRB$W_NID_RIGHT = 160,0,16,0 %;
1247 0 macro IRB$W_NID_MID = 162,0,16,0 %;
1248 0 macro IRB$W_RFA_NID = 164,0,16,0 %;
1249 0 macro IRB$B_KEYSZ = 166,0,8,0 %;
1250 0 macro IRB$L_CUR_VBN = 168,0,32,0 %;
1251 0 macro IRB$L_POS_VBN = 172,0,32,0 %;
1252 0 macro IRB$L_UDR_VBN = 176,0,32,0 %;
1253 0 macro IRB$L_SIDR_VBN = 180,0,32,0 %;
1254 0 macro IRB$W_CUR_ID = 184,0,16,0 %;
1255 0 macro IRB$W_POS_ID = 186,0,16,0 %;
1256 0 macro IRB$W_UDR_ID = 188,0,16,0 %;
1257 0 macro IRB$W_SIDR_ID = 190,0,16,0 %;
1258 0 macro IRB$W_CUR_COUNT = 192,0,16,0 %;
1259 0 macro IRB$B_RP_KREF = 194,0,8,0 %;
1260 0 macro IRB$B_CUR_KREF = 195,0,8,0 %;
1261 0
1262 0 *** MODULE $ASBDEF ***
1263 0
1264 0 ASB field definitions
1265 0
1266 0 Asynchronous context block (asb)
1267 0
1268 0 There is one asb per irab pointed to by irb$L_asbaddr allocated at
1269 0 connect and one per ifab which is dynamically allocated at stall
1270 0
1271 0 The asb$L_arglst is pointed to by the arglst field of the
1272 0 irab if the irb$V_async bookkeeping bit is set
1273 0
1274 0 All of the asb$c_bln_xxx must be longword aligned
1275 0
1276 0 literal ASB$c_BID = 13;
1277 0 literal ASB$c_BLN_FIX = 48;
1278 0 literal ASB$c_BLN_FIX = 48;
1279 0 ! regs 4 and 5 are saved on stack
1280 0 literal ASB$c_BLN_SEQ = 188;
1281 0 literal ASB$c_BLN_SEQ = 188;
1282 0 literal ASB$c_BLN_REL = 192;
1283 0 literal ASB$c_BLN_REL = 192;
1284 0 literal ASB$c_BLN_FAB = 352;
1285 0 literal ASB$c_BLN_FAB = 352;
1286 0 literal ASB$c_BLN_IDX = 512;
1287 0 literal ASB$c_BLN_IDX = 512;
1288 0 literal ASB$c_ASBDDEF = 512;
1289 0 macro ASB$W_STKLEN = 0,0,16,0 %;
1290 0 ! STKLEN = BLN org - BLN_FIX
1291 0 macro ASB$W_STKSIZ = 2,0,16,0 %;
1292 0 macro ASB$B_BID = 8,0,8,0 %;
1293 0 macro ASB$B_BLN = 9,0,8,0 %;
1294 0 macro ASB$L_ARGLIST = 12,0,0,0 %;

```

```

temporary two for make index
middle vbn of split
temporary three for make index
used by search tree
number of current record in this bucket (plg 3)
address of last key with zero front compression (plg 3)
number of the first record to be moved into new bucket

Next record ID of the right bucket
Next record ID of the middle bucket
Next record ID of the RFA bucket
size of key in keybuffer !2
VBN of current record (primary/SIDR)
VBN of primary data record for NRP positioning
VBN of current primary data record
SIDR array first element VBN of current record (SIDR)
ID of current record (primary)
ID of primary data record for NRP positioning
ID of current primary data record
SIDR array first element ID of current record (SIDR)
SIDR array count of current record (SIDR)
Key of reference by which next record is retrieved
Key of reference of current record (primary/SIDR)

```

```

asb id = 13
block length of fixed asb
block length of fixed asb

block length for seq org irab operations
block length for seq org irab operations
block length for rel org irab operations
block length for rel org irab operations
block length for fab-related operations
block length for fab-related operations

! save stack length (must be first word in block)

size of saved stack in bytes
block id
block length in longwords

```



```

1295 0 literal ASB$$ ARGST = 16;
1296 0 macro ASB$$ ARGCNT = 12,0,8,0 %;
1297 0 ! value will be 0, 1, 2, or 3
1298 0 macro ASB$$ FABRAB = 16,0,32,0 %;
1299 0 macro ASB$$ ERR = 20,0,32,0 %;
1300 0 macro ASB$$ SUC = 24,0,32,0 %;
1301 0 macro ASB$$ REGS = 28,0,0,0 %;
1302 0 literal ASB$$ REGS = 20;
1303 0 macro ASB$$ STK = 48,0,0,0 %;
1304 0 literal ASB$$ STK = 140;
1305 0
1306 0 *** MODULE $BDBDEF ***
1307 0
1308 0 BDB field definitions
1309 0
1310 0 buffer descriptor block (bdb)
1311 0
1312 0 there is one bdb per i/o buffer
1313 0 ( the i/o buffers exist in separate pages, page aligned)
1314 0
1315 0 literal BDB$$ BID = 12;
1316 0 literal BDB$$ VAL = 1;
1317 0 literal BDB$$ DRT = 2;
1318 0 literal BDB$$ IOP = 4;
1319 0 literal BDB$$ PRM = 8;
1320 0 literal BDB$$ NOLOCATE = 16;
1321 0 literal BDB$$ WFO = 32;
1322 0 literal BDB$$ AST DCL = 64;
1323 0 literal BDB$$ BDBDEF = 80;
1324 0 macro BDB$$ FLINK = 0,0,32,0 %;
1325 0 macro BDB$$ BLINK = 4,0,32,0 %;
1326 0 macro BDB$$ BID = 8,0,8,0 %;
1327 0 macro BDB$$ BLN = 9,0,8,0 %;
1328 0 macro BDB$$ FLGS = 10,0,8,0 %;
1329 0 macro BDB$$ VAL = 10,0,1,0 %;
1330 0 macro BDB$$ DRT = 10,1,1,0 %;
1331 0 macro BDB$$ IOP = 10,2,1,0 %;
1332 0 macro BDB$$ PRM = 10,3,1,0 %;
1333 0 macro BDB$$ NOLOCATE = 10,4,1,0 %;
1334 0 macro BDB$$ WFO = 10,5,1,0 %;
1335 0 macro BDB$$ AST DCL = 10,6,1,0 %;
1336 0 ! waiting stream
1337 0 ! the releasing of this bdb
1338 0 ! (set/cleared by rm$cache)
1339 0 macro BDB$$ CACHE VAL = 11,0,8,0 %;
1340 0 macro BDB$$ VERTYP = 11,0,8,0 %;
1341 0 macro BDB$$ USERS = 12,0,16,0 %;
1342 0 macro BDB$$ BUFF ID = 14,0,16,0 %;
1343 0 macro BDB$$ BLB PTR = 16,0,32,0 %;
1344 0 macro BDB$$ NUMB = 20,0,16,0 %;
1345 0 macro BDB$$ DIRSEQ = 20,0,16,0 %;
1346 0 macro BDB$$ SIZE = 22,0,16,0 %;
1347 0 macro BDB$$ ADDR = 24,0,32,0 %;
1348 0 macro BDB$$ VBN = 28,0,32,0 %;
1349 0 macro BDB$$ VBNSEQNO = 32,0,32,0 %;
1350 0 macro BDB$$ LAST = 32,0,32,0 %;
1351 0 macro BDB$$ WAIT = 36,0,32,0 %;

```

! saved argument list on async irab operations
! argument count
! fab or rab address
! err routine addr
! suc routine addr
! save register area for regs 6, 7, 8, 10 and 11
! saved stack area
! bdb id code
! forward link
! backward link
! block id
! block length in longwords
! bdb flags
! buffer contents valid
! buffer content dirty
! buffer has i/o in progress
! buffer has permanence factor
! buffer shared - no locate mode
! other streams awaiting
! ast has been declared for
! relative value of buffer in cache
! version type (1 = wild)
! number of streams referencing this buffer
! buffer identification number
! pointer to BLB chain for this BDB
! of bytes of buffer in use
! UCB\$\$ DIRSEQ at directory read time
! bytes in buffer
! address of buffer
! 1st vbn in buffer
! vbn seq number of validity check vs. bcb copy
! address of last directory record
! wait thread (irab addr)

C 3
15-Sep-1984 22:56:58
15-Sep-1984 22:56:57


VAX-11 Bliss-32 V4.0-742
_S255\$DUA28:[RMS.OBJ]RMSINTDEF.R32;1 Page 29
(9)

```
1352 0 ! (for inter-stream intra-
1353 0 ! process locking only)
1354 0 macro BDB$L_VERCOUNT = 36,0,32,0 %; ! negative count of version entries scanned
1355 0 macro BDB$L_ALLOC_ADDR = 40,0,32,0 %; ! buffer allocation addr
1356 0 macro BDB$W_ALLOC_SIZE = 44,0,16,0 %; ! buffer allocation size
1357 0 macro BDB$L_BI_BDB = 48,0,32,0 %; ! address of isam/block i/o bi journaling BDB
1358 0 macro BDB$L_AI_BDB = 52,0,32,0 %; ! address of isam/block i/o ai journaling BDB
1359 0 macro BDB$T_JNLSEQ = 56,0,0,0 %;
1360 0 literal BDB$S_JNLSEQ = 16; ! Journaling Sequence Number Block
1361 0 macro BDB$L_WK1 = 72,0,32,0 %; ! work area
1362 0 macro BDB$B_REL_VBN = 72,0,8,0 %; ! current vbn rel to start of buffer
1363 0 macro BDB$B_VAL_VBNS = 73,0,8,0 %; ! of valid vbns in buffer
1364 0 macro BDB$B_PRE_CCTL = 74,0,8,0 %; ! unit record carriage control byte ('pre')
1365 0 macro BDB$B_POST_CCTL = 75,0,8,0 %; ! unit record carriage control byte ('post')
1366 0 macro BDB$L_CURBUFADR = 76,0,32,0 %; ! current buffer addr
1367 0 literal BDB$K_BLN = 80; ! length of bdb block
1368 0 literal BDB$C_BLN = 80; ! length of bdb block
1369 0 literal BDB$S_BDBDEF1 = 80;
1370 0 macro BDB$L_IOSB = 72,0,0,0 %;
1371 0 literal BDB$S_IOSB = 8; ! i/o status block for buffer
1372 0 macro BDB$L_VERSION = 72,0,32,0 %; ! addr of current/next directory version entry
1373 0 macro BDB$L_RECORD = 76,0,32,0 %; ! address of current/next directory record
1374 0
1375 0 !*** MODULE $GBPBDEF ***
1376 0
1377 0 !
1378 0 ! GBPB field definitions
1379 0 !
1380 0 ! Global Buffer Pointer Block (GBPB)
1381 0 !
1382 0 ! The GBPB is the process local structure used in conjunction with
1383 0 ! shared global i/o buffers. In order to minimize the impact of
1384 0 ! global buffers on existing code, the GBPB is identical to a BDB
1385 0 ! in those fields which are referenced outside of the RM$CACHE and
1386 0 ! RM$RELEASE routines.
1387 0 !
1388 0 ! literal GBP$C_BID = 21; ! gbp id code
1389 0 ! literal GBP$K_BLN = 40; ! Length of GBP block
1390 0 ! literal GBP$C_BLN = 40; ! Length of GBP block
1391 0 ! literal GBP$S_GBPDDEF = 40;
1392 0 ! macro GBP$L_FLINK = 0,0,32,0 %; ! forward link
1393 0 ! macro GBP$L_BLINK = 4,0,32,0 %; ! backward link
1394 0 ! macro GBP$B_BID = 8,0,8,0 %; ! block id
1395 0 ! macro GBP$B_BLN = 9,0,8,0 %; ! block length in longwords
1396 0 ! macro GBP$B_FLGS = 10,0,8,0 %; ! gbp flags (use BDB flgs definitions)
1397 0 ! macro GBP$B_CACHE_VL = 11,0,8,0 %; ! relative cache value of this buffer
1398 0 ! macro GBP$W_USERS = 12,0,16,0 %; ! number of streams referencing this buffer
1399 0 ! macro GBP$W_BUFF_ID = 14,0,16,0 %; ! buffer identification number
1400 0 ! macro GBP$L_BLB_PTR = 16,0,32,0 %; ! pointer to BLB chain for this GBPB
1401 0 ! macro GBP$W_NUMB = 20,0,16,0 %; ! of bytes of buffer in use
1402 0 ! macro GBP$L_ADDR = 24,0,32,0 %; ! bytes in buffer
1403 0 ! macro GBP$L_VBN = 28,0,32,0 %; ! address of buffer
1404 0 ! macro GBP$L_VBNSEQNO = 32,0,32,0 %; ! 1st vbn in buffer
1405 0 ! macro GBP$L_GBD_PTR = 36,0,32,0 %; ! sequence number field.
1406 0 ! ! Pointer to the GBD for this buffer.
1407 0 !
1408 0 !*** MODULE $RLBDEF ***
1409 0 !
```


RLB field definitions

record lock block (rlb)

The rlb describes one locked record for a particular process-record stream (rab/irab). if the owner field is 0 then the rlb is available for use. otherwise, it describes a locked record. note: when owner is 0 the record rfa fields are zeroed (0).



literal RLBSM_TIMER_INPROG = 1;

literal RLBSM_BID = 14;

literal RLBSM_WAIT = 1;

literal RLBSM_CR = 2;

literal RLBSM_PW = 4;

literal RLBSM_PR = 8;

literal RLBSM_CONV = 16;

literal RLBSM_LV2 = 32;

literal RLBSM_FAKE = 64;

literal RLBSM_TMO = 128;

literal RLBSK_BLN = 28;

literal RLBSK_BLN = 28;

literal RLBSM_RLBDEF = 28;

macro RLBSL_LNK = 0,0,32,0 %;

macro RLBSL_MISC = 4,0,32,0 %;

macro RLBSW_FLAGS2 = 4,0,16,0 %;

macro RLBSV_TIMER_INPROG = 4,0,1,0 %;

macro RLBSW_RFA4 = 6,0,16,0 %;

! offset for seq f.o. (bits 0:14)

! always 0 for rel f.o. (bits 0:14)

macro RLBSW_ID = 6,0,16,0 %;

macro RLBSB_BID = 8,0,8,0 %;

macro RLBSB_BLN = 9,0,8,0 %;

macro RLBSB_TMO = 10,0,8,0 %;

macro RLBSB_FLAGS = 11,0,8,0 %;

macro RLBSV_WAIT = 11,0,1,0 %;

macro RLBSV_CR = 11,1,1,0 %;

macro RLBSV_PW = 11,2,1,0 %;

! rlb code

! length of rlb

! length of rlb

! link to next rlb

! longword definition to optimize clearing field

! more flag bits

! Timer queued.

! 3'rd word of records rfa

! id for idx f.o.

! block id

! block length in longwords

! propagation of ROP TMO field

! various locking flags

! propagation of ROP WAT bit

! defines lock manager mode "concurrent read"

! allow reader access to locked record flag

E 3
15-Sep-1984 22:56:58
15-Sep-1984 22:56:57

VAX-11 Bliss-32 V4.0-742
_S255SDUA28:[RMS.OBJ]RMSINTDEF.R32;1

Page 31
(9)

```
1466 0 macro RLBSV_PR = 11,3,1,0 %;
1467 0 macro RLBSV_CONV = 11,4,1,0 %;
1468 0 macro RLBSV_LV2 = 11,5,1,0 %;
1469 0 macro RLBSV_FAKE = 11,6,1,0 %;
1470 0 macro RLBSV_TMO = 11,7,1,0 %;
1471 0 ! indicate "lock for write, allow readers"
1472 0 ! used to query lock database for records
1473 0 macro RLBSL_RFA0 = 12,0,32,0 %;
1474 0 ! seq f.o. vbn
1475 0 ! rel f.o. relative record number
1476 0 ! idx f.o. start vbn
1477 0 macro RLBSL_OWNER = 16,0,32,0 %;
1478 0 macro RLBSL_LKSB = 20,0,32,0 %;
1479 0 macro RLBSW_STATUS = 20,0,16,0 %;
1480 0 macro RLBSW_S_BITS = 22,0,16,0 %;
1481 0 macro RLBSL_LOCK_ID = 24,0,32,0 %;
1482 0
1483 0 !*** MODULE $FLBDEF ***
1484 0
1485 0 ! file lock block definitions
1486 0
1487 0 literal FLBSC_BID = 23;
1488 0 literal FLBSK_BLN = 20;
1489 0 literal FLBSC_BLN = 20;
1490 0 literal FLBSS_FLBDEF = 20;
1491 0 macro FLBSL_FLB_LNK = 0,0,32,0 %;
1492 0 macro FLBSL_RLB_LNK = 4,0,32,0 %;
1493 0 macro FLBSB_BID = 8,0,8,0 %;
1494 0 macro FLBSB_BLN = 9,0,8,0 %;
1495 0 macro FLBSL_IFB_PTR = 12,0,32,0 %;
1496 0 macro FLBSL_LOCK_ID = 16,0,32,0 %;
1497 0
1498 0 !*** MODULE $DRCDEF ***
1499 0
1500 0 ! directory cache node definitions
1501 0
1502 0 literal DRC$K_BLN = 62;
1503 0 literal DRC$C_BLN = 62;
1504 0 literal DRC$S_DRCDEF = 62;
1505 0 macro DRC$N_NXTFLNK = 0,0,32,0 %;
1506 0 macro DRC$N_NXTBLNK = 4,0,32,0 %;
1507 0 macro DRC$N_LVLFLNK = 8,0,32,0 %;
1508 0 macro DRC$N_LVLBLNK = 12,0,32,0 %;
1509 0 ! note: the links are maintained in lru order
1510 0 macro DRC$T_NAME = 16,0,0,0 %;
1511 0 literal DRC$S_NAME = 40;
1512 0 ! note: stored as counted string counting count itself
1513 0 macro DRC$W_DID = 56,0,0,0 %;
1514 0 literal DRC$S_DID = 6;
1515 0 macro DRC$W_DIRSEQ = 58,0,16,0 %;
1516 0
1517 0 !*** MODULE $RLSDEF ***
1518 0
1519 0 ! release option flag definitions
1520 0
1521 0 literal RL$M_RETURN = 1;
1522 0 literal RL$M_WRT_THRU = 2;
```

used to query lock database
defines lock manager option "convert"
sets lock as "level 2" RU consistency
this RLB contains no lock.
propagation of ROP TMO bit
1'st and 2'nd words of record's rfa
identification of owning stream
first longword of lock status block
VMS status code
various status bits
second longword of lkbs is lock_id
pointer to next FLB
pointer to RLBs
block id
block length
IFAB address
lock id
length of directory cache node
length of directory cache node
link to next entry, this level
link to previous entry, this level
link to first entry, next lower level
link to last entry, next lower level
directory name or device and unit
file id for directory
directory sequence ! for device node


```

1523 0 literal RLSSM_KEEP_LOCK = 4;
1524 0 literal RLSSM_DEQ = 8;
1525 0 literal RLSSS_RLSDEF = 1;
1526 0 macro RLSSV_RETURN = 0,0,1,0 %;      ! return buffer and bdb to free space lists
1527 0 macro RLSSV_WRT_THRU = 0,1,1,0 %;   ! write buffer if dirty
1528 0 macro RLSSV_KEEP_LOCK = 0,2,1,0 %;  ! keep bdb locked
1529 0 macro RLSSV_DEQ = 0,3,1,0 %;        ! always release lock
1530 0
1531 0 *** MODULE $CSHDEF ***
1532 0
1533 0         cache option flag definitions
1534 0
1535 0 literal CSHSM_LOCK = 1;
1536 0 literal CSHSM_NOWAIT = 2;
1537 0 literal CSHSM_NOREAD = 4;
1538 0 literal CSHSM_NOBUFFER = 8;
1539 0 literal CSHSS_CSHDEF = 1;
1540 0 macro CSHSV_LOCK = 0,0,1,0 %;         ! obtain exclusive access to block
1541 0 macro CSHSV_NOWAIT = 0,1,1,0 %;      ! do not wait for block on access interlock
1542 0 macro CSHSV_NOREAD = 0,2,1,0 %;     ! do not read in block
1543 0 macro CSHSV_NOBUFFER = 0,3,1,0 %;    ! obtain access to block but don't allocate
1544 0 ! a buffer for it and don't read it
1545 0 ! collision
1546 0
1547 0 *** MODULE $PIODEF ***
1548 0
1549 0         rms overall status bit definitions
1550 0
1551 0 literal PIOSS_PIODEF = 1;
1552 0 macro PIO$V_INHA$T = 0,0,1,0 %;      ! set if asts implicitly inhibited
1553 0 ! if reset by disabled ast, ast must be re-
1554 0 ! enabled
1555 0 macro PIO$V_EOD = 0,1,1,0 %;         ! set if searching for 'eod' string on 'input'
1556 0 macro PIO$V_SYNC1 = 0,2,1,0 %;      ! sync stalled operation using efn 27
1557 0 macro PIO$V_SYNC2 = 0,3,1,0 %;      ! sync stalled operation using efn 28
1558 0
1559 0 *** MODULE $FTLDEF ***
1560 0
1561 0         definitions for rms debug failure codes
1562 0
1563 0
1564 0         the following codes are for temporary bug check tests, and are
1565 0         internal to rms. all of the codes are negative, implying that they
1566 0         do not return to the caller, probably killing the process (if not
1567 0         the entire system).
1568 0
1569 0
1570 0 literal FTL$_SETPRTFAIL = -1;          ! set protection system service failed (rm0bufmgr)
1571 0 literal FTL$_STKTOOBIG = -2;          ! stack too big for asb (rm0stall)
1572 0 literal FTL$_BADIFAB = -3;            ! invalid ifab or irab (rm0fset,rm0conn,rm0rset,rm0prflnm)
1573 0 literal FTL$_GTCHNFAIL = -4;          ! get channel system service failure (rm0prflnm)
1574 0 literal FTL$_BADORGCASE = -5;         ! invalid orgcase value for dispatch (all rms$
1575 0 ! level routines except open and create)
1576 0 literal FTL$_BADBDB = -6;             ! block not a bdb (rm0bufmgr)
1577 0 literal FTL$_ASBALLFAIL = -7;         ! couldn't allocate an asb (rm0stall)
1578 0 literal FTL$_BADASTPRM = -8;          ! ast parameter not a valid ifab/irab addr (rm0stall)
1579 0 literal FTL$_CANTDOAST = -9;          ! couldn't redeclare ast (insf. mem.) (rm0stall)

```



```

1580 0 literal FTL$_NOSTRUCT = -10;      ! rab or fab not same on ast (rm0stall)
1581 0 literal FTL$_NOASB = -11;        ! asb not allocated or stream not busy on ast (rm0stall)
1582 0 literal FTL$_NONXTBDB = -12;     ! no next bdb available (rm1seqxfr)
1583 0 literal FTL$_BADBUFSIZ = -13;    ! disk buffer size not = 512 (rm1conn)
1584 0 literal FTL$_ENQDEQFAIL = -14;   ! enq or deq service failed (rm0reclck)
1585 0 literal FTL$_NOCURBDB = -15;     ! no current bdb before calling rm$release (rm0reclck)
1586 0 literal FTL$_NOPARENT = -16;     ! no parent lock available for global buffer section lock (rm0share)
1587 0 literal FTL$_DEALLERR = -17;     ! ifab deallocation attempted with other block(s)
1588 0 ! still allocated (rms0close)
1589 0 literal FTL$_IORNDN = -18;        ! i/o rundown inconsistency (either ifab or irab)
1590 0 ! table entries not zeroed) (rms0rndwn)
1591 0 literal FTL$_XFERSIZE = -19;      ! size of requested transfer not equal to
1592 0 ! or less than the current number of bytes
1593 0 ! in use for the bdb (rm0cache)
1594 0 literal FTL$_NOTLOCKED = -20;     ! bdb not locked and a keep lock request
1595 0 ! was made on a release request.
1596 0 literal FTL$_NODIDORFID = -21;    ! neither a fid nor a did was set upon exit from
1597 0 ! rm$setdid (rms0erase)
1598 0 literal FTL$_RELEASFAIL = -22;    ! release of non-dirty bdb failed (rm0xtnd23,rms0extend)
1599 0 literal FTL$_NOLOCKBDB = -23;    ! no lock bdb found (rm0xtnd23)
1600 0 literal FTL$_NONETWORK = -24;    ! network routine entered but no network support in rms
1601 0 literal FTL$_LOCKFAILED = -25;    ! failed to lock prolog (rm2create)
1602 0 literal FTL$_BADLEVEL = -26;     ! to search by id, structure level must be 0
1603 0 literal FTL$_ASTDECERR = -27;     ! ast declaration for file sharing failed
1604 0 literal FTL$_BADGBLCNT = -28;    ! Zero global buffer count found when not expected (rm1conn)
1605 0 literal FTL$_ACCNTOVFLO = -29;    ! access count overflow (rm0share)
1606 0 literal FTL$_BDBAVAIL = -30;     ! BDB was available and shouldn't have been.
1607 0 literal FTL$_GBLNOLK = -31;     ! Record locking was not set with global buffers.
1608 0 literal FTL$_LCKFND = -32;       ! A lock was found and we don't know what to do.
1609 0 literal FTL$_NOBLB = -33;        ! No BLB was found and there should have been one.
1610 0 literal FTL$_NOGBPB = -34;       ! No GBPB was found and should have been.
1611 0 literal FTL$_NOLCLBUF = -35;     ! Should have found a local buffer.
1612 0 literal FTL$_NORDNOTSET = -36;   ! NOREAD not set when NOBUFFER was.
1613 0 literal FTL$_NOTGBPB = -37;      ! Found an illegit BDB.
1614 0 literal FTL$_NOSFSB = -38;       ! No SFSB when allocating BLB.
1615 0 literal FTL$_LOCKHELD = -39;     ! Attempted to return a BLB with lock_id neq 0
1616 0 literal FTL$_RLSDRT = -40;       ! Dirty buffer found in releasall.
1617 0 literal FTL$_BADBLB = -41;       ! Bad BLB found in blocking AST routine.
1618 0 literal FTL$_BADOWNER = -42;     ! Owner field in BLB is bad in blocking AST routine.
1619 0 literal FTL$_GETLKIFAIL = -43;    ! $GETLKIW failed in last chance (rms0lstch).
1620 0 literal FTL$_BADEBKHBK = -44;    ! tried to store an invalid EBK/HBK (rm0share).

```

```

1621 0
1622 0 *** MODULE $BUGDEF ***

```

```

1623 0
1624 0 the following internal codes are for non-fatal bug check reporting.
1625 0 these codes are positive byte values. they trigger a reporting action
1626 0 and return to the caller with r0 set to rms$_bug+<8*the bug code>,
1627 0 which is an externally documented rms error code.

```

```

1628 0
1629 0 literal BUG$_BADDFLTDIR = 1;          ! DEFAULT DIRECTORY STRING INVALID (RMOXPFN)

```

```

1630 0
1631 0 *** MODULE $IDXDEF ***

```

```

1632 0
1633 0     IDX field definitions

```

```

1634 0
1635 0     index descriptor definition
1636 0

```



```

1637 0      |
1638 0      |
1639 0      |
1640 0      | literal IDX$C_BID = 15;      | id for index descriptor block
1641 0      | literal IDX$M-DUPKEYS = 1;
1642 0      | literal IDX$M-CHGKEYS = 2;
1643 0      | literal IDX$M-NULKEYS = 4;
1644 0      | literal IDX$M-IDX_COMPR = 8;
1645 0      | literal IDX$M-INITIDX = 16;
1646 0      | literal IDX$M-KEY_COMPR = 64;
1647 0      | literal IDX$M-REC_COMPR = 128;
1648 0      | literal IDX$C-STRING = 0;   | string data type
1649 0      | literal IDX$C-SGNWORD = 1;  | signed binary word
1650 0      | literal IDX$C-UNSGNWORD = 2; | unsigned binary word
1651 0      | literal IDX$C-SGNLONG = 3;  | signed binary long word
1652 0      | literal IDX$C-UNSGNLONG = 4; | unsigned binary long word
1653 0      | literal IDX$C-PACKED = 5;   | packed decimal
1654 0      | literal IDX$C-SGNQUAD = 6;  | signed binary quadword
1655 0      | literal IDX$C-UNSGNQUAD = 7; | unsigned binary quadword
1656 0      | literal IDX$C-V2_BKT = 0;   | Prologue two bucket
1657 0      | literal IDX$C-CMPIDX = 1;   | Prologue 3, index keys are compressed
1658 0      | literal IDX$C-NCMPIDX = 2;  | Prologue 3, index keys are not compressed
1659 0      | literal IDX$C-CMPCMP = 3;   | Prologue 3, primary key is compressed, data
1660 0      | is compressed
1661 0      | Prologue 3, SDR key is compressed
1662 0      | literal IDX$C-CMPNCMP = 4;   | Prologue 3, primary key is compressed,
1663 0      | data is not compressed
1664 0      | literal IDX$C-NCMPCMP = 5;   | Prologue 3, primary key is not compressed
1665 0      | data is compressed
1666 0      | literal IDX$C-NCMPNCMP = 6;  | Prologue 3, primary key is not compressed
1667 0      | data is not compressed
1668 0      | Prologue 3, SDR key is compressed
1669 0      | literal IDX$K_FIXED_BLN = 44;
1670 0      | literal IDX$C_FIXED_BLN = 44;
1671 0      |
1672 0      | the following is the length of the fixed part of the index descriptor
1673 0      |
1674 0      |
1675 0      | the following is repeated for each key segment
1676 0      |
1677 0      | literal IDX$S_IDXDEF = 48;
1678 0      | macro IDX$S_IDXFL = 0,0,32,0 %; | forward link to next index descriptor
1679 0      | macro IDX$B_BID = 8,0,8,0 %;    | block id
1680 0      | macro IDX$B_BLN = 9,0,8,0 %;    | length of block
1681 0      | macro IDX$S_VBN = 10,0,32,0 %;  | VBN where the descriptor came from
1682 0      | macro IDX$W_OFFSET = 14,0,16,0 %; | Offset into the block (VBN) of the descriptor
1683 0      | macro IDX$B_DESC_NO = 16,0,8,0 %; | Descriptor number (index into update buffer)
1684 0      | macro IDX$B_IANUM = 18,0,8,0 %;  | area number for index buckets
1685 0      | macro IDX$B_LANUM = 19,0,8,0 %;  | area number for lower index buckets
1686 0      | macro IDX$B_DANUM = 20,0,8,0 %;  | area number for data buckets
1687 0      | macro IDX$B_ROOTLEV = 21,0,8,0 %; | level of root
1688 0      | macro IDX$B_IDXBKTSZ = 22,0,8,0 %; | size of index bucket in vbn's
1689 0      | macro IDX$B_DATBKTSZ = 23,0,8,0 %; | size of data bucket in vbn's
1690 0      | macro IDX$S_ROOTVBN = 24,0,32,0 %; | start vbn of root bucket
1691 0      | macro IDX$B_FLAGS = 28,0,8,0 %;  | index/key flags
1692 0      | macro IDX$V-DUPKEYS = 28,0,1,0 %; | duplicate keys allowed
1693 0      | macro IDX$V-CHGKEYS = 28,1,1,0 %; | keys can change values

```



```

1694 0 macro IDXSV_NULKEYS = 28,2,1,0 %: ! null key value allowed
1695 0 macro IDXSV_IDX_COMPR = 28,3,1,0 %: ! index is compressed
1696 0 macro IDXSV_INITIDX = 28,4,1,0 %: ! index is not initialized
1697 0 macro IDXSV_KEY_COMPR = 28,6,1,0 %: ! key has been compressed
1698 0 macro IDXSV_REC_COMPR = 28,7,1,0 %: ! data record is in compressed form
1699 0 macro IDXSB_DATATYPE = 29,0,8,0 %: ! data type of key field
1700 0 macro IDXSB_SEGMENTS = 30,0,8,0 %: ! number of key field segments
1701 0 macro IDXSB_NULLCHAR = 31,0,8,0 %: ! null character
1702 0 macro IDXSB_KEYSZ = 32,0,8,0 %: ! total key size
1703 0 macro IDXSB_KEYREF = 33,0,8,0 %: ! key of reference(0-primary)
1704 0 macro IDXSW_MINRECSZ = 34,0,16,0 %: ! minimum record size
1705 0 macro IDXSW_IDXFILL = 36,0,16,0 %: ! index fill
1706 0 macro IDXSW_DATAFILL = 38,0,16,0 %: ! data fill
1707 0 macro IDXSB_IDXBKTYTYP = 40,0,8,0 %: ! PLG3 - type of index bucket and SIDR bucket
1708 0 macro IDXSB_DATABKTYTYP = 41,0,8,0 %: ! PLG3 - type of primary data bucket
1709 0 macro IDXSW_POSITION = 44,0,16,0 %: ! key segment position
1710 0 macro IDXSB_SIZE = 46,0,8,0 %: ! key segment size (plg 3)
1711 0 macro IDXSB_TYPE = 47,0,8,0 %: ! key segment datatype (plg 3)
1712 0
1713 0 !*** MODULE $UPDDEF ***
1714 0
1715 0 ! update buffer flags
1716 0
1717 0 literal UPDSM_INS_NEW = 1;
1718 0 literal UPDSM_OLD_DEL = 2;
1719 0 literal UPDSS_UPDDEF = 1;
1720 0 macro UPDSB_FLAGS = 0,0,8,0 %:
1721 0 macro UPDSV_INS_NEW = 0,0,1,0 %: ! alternate key to be inserted from record buffer
1722 0 macro UPDSV_OLD_DEL = 0,1,1,0 %: ! delete this key value using old record
1723 0
1724 0 !*** MODULE $GBHDEF ***
1725 0
1726 0 ! GBH field definitions
1727 0
1728 0 ! Global Buffer Header (GBH)
1729 0
1730 0 ! There is a Global Buffer Header for every file's global buffer section.
1731 0
1732 0 !*** WARNING - THIS STRUCTURE MUST BE QUADWORD ALIGNED ***
1733 0
1734 0 ! Block ID code for GBH
1735 0 literal GBHSC_BID = 17;
1736 0 literal GBHSM_CACHE_IN = 1;
1737 0 literal GBHSM_CACHE_OUT = 2;
1738 0 literal GBHSM_RLS_IN = 4;
1739 0 literal GBHSM_RLS_OUT = 8;
1740 0 literal GBHSM_QIO_START = 16;
1741 0 literal GBHSM_QIO_DONE = 32;
1742 0 literal GBHSM_STACL = 64;
1743 0 literal GBHSM_THREADGO = 128;
1744 0 literal GBHSM_BLB_ENQ = 256;
1745 0 literal GBHSM_BLB_GRANT = 512;
1746 0 literal GBHSM_BLB_DEQ = 1024;
1747 0 literal GBHSM_BLB_BLOCK = 2048;
1748 0 literal GBHSM_F1 = 4096;
1749 0 literal GBHSM_F2 = 8192;
1750 0 literal GBHSM_F3 = 16384;
1751 0 literal GBHSM_F4 = 32768;

```



```

1751 0 literal GBH$K_BLN = 88;
1752 0 literal GBH$C_BLN = 88;
1753 0 literal GBH$$GBHDEF = 88;
1754 0 macro GBH$L_GBD_FLNK = 0,0,32,0 %;
1755 0 macro GBH$L_GBD_BLNK = 4,0,32,0 %;
1756 0 macro GBH$B_BID = 8,0,8,0 %;
1757 0 macro GBH$B_BLN = 9,0,8,0 %;
1758 0 macro GBH$W_TRC_FLGS = 10,0,16,0 %;
1759 0 macro GBH$V_CACHE_IN = 10,0,1,0 %;
1760 0 macro GBH$V_CACHE_OUT = 10,1,1,0 %;
1761 0 macro GBH$V_RLS_IN = 10,2,1,0 %;
1762 0 macro GBH$V_RLS_OUT = 10,3,1,0 %;
1763 0 macro GBH$V_QIO_START = 10,4,1,0 %;
1764 0 macro GBH$V_QIO_DONE = 10,5,1,0 %;
1765 0 macro GBH$V_STALL = 10,6,1,0 %;
1766 0 macro GBH$V_THREADGO = 10,7,1,0 %;
1767 0 macro GBH$V_BLB_ENQ = 10,8,1,0 %;
1768 0 macro GBH$V_BLB_GRANT = 10,9,1,0 %;
1769 0 macro GBH$V_BLB_DEQ = 10,10,1,0 %;
1770 0 macro GBH$V_BLB_BLOCK = 10,11,1,0 %;
1771 0 macro GBH$V_F1 = 10,12,1,0 %;
1772 0 macro GBH$V_F2 = 10,13,1,0 %;
1773 0 macro GBH$V_F3 = 10,14,1,0 %;
1774 0 macro GBH$V_F4 = 10,15,1,0 %;
1775 0 macro GBH$L_HI_VBN = 12,0,32,0 %;
1776 0 macro GBH$L_GS_SIZE = 16,0,32,0 %;
1777 0 macro GBH$L_LOCK_ID = 20,0,32,0 %;
1778 0 macro GBH$L_GS_LOCK_ID = 24,0,32,0 %;
1779 0 macro GBH$L_USECNT = 28,0,32,0 %;
1780 0 macro GBH$L_TRC_FLNK = 32,0,32,0 %;
1781 0 macro GBH$L_TRC_BLNK = 36,0,32,0 %;
1782 0 macro GBH$L_GBD_START = 40,0,32,0 %;
1783 0 macro GBH$L_GBD_END = 44,0,32,0 %;
1784 0 macro GBH$L_GBD_NEXT = 48,0,32,0 %;
1785 0 macro GBH$L_SCAN_NUM = 52,0,32,0 %;
1786 0
1787 0 Global buffer statistics section
1788 0
1789 0 macro GBH$L_HIT = 56,0,32,0 %;
1790 0 macro GBH$L_MISS = 60,0,32,0 %;
1791 0 macro GBH$L_READ = 64,0,32,0 %;
1792 0 macro GBH$L_WRITE = 68,0,32,0 %;
1793 0 macro GBH$L_DFW_WRITE = 72,0,32,0 %;
1794 0 macro GBH$L_CROSS_HIT = 76,0,32,0 %;
1795 0 macro GBH$L_OUTBUFQUO = 80,0,32,0 %;
1796 0 macro GBH$L_FILL_1 = 84,0,32,0 %;
1797 0
1798 0 *** MODULE $TRCDEF ***
1799 0
1800 0 TRC field definitions
1801 0
1802 0 Trace block structure (TRC)
1803 0
1804 0 Tracing saves at specific points in the RMS code for debugging and
1805 0 algorithm analysis purposes.
1806 0
1807 0 *** WARNING - THIS STRUCTURE MUST BE QUADWORD ALIGNED ***

```

```

! Length of global buffer header structure
! Length of global buffer header structure
! Self relative queue header for GBD's
!
! Block ID
! Length of GBH in longwords
! Trace flags (set to trace given function)
! Cache inputs
! Cache outputs
! Release inputs
! Release outputs
! Qio inputs
! Qio outputs
! Stall inputs
! Stall outputs
! Bucket lock ENQ inputs
! Bucket lock grant status
! Bucket lock DEQ request
! Blocking AST received
!
!
! Highest possible VBN value (FFFFFFFF).
! Size of total section in bytes.
! Lock ID of system file lock.
! Lock ID of system global section lock.
! Accessor count for section.
! Trace blocks forward link
! Trace blocks back link
! Offset to first GBD.
! Offset to last GBD.
! Offset to next cache victim GBD.
! Number of GBD's to scan for victim.
!
! Buffer found in global cache
! Buffer not found in global cache
! Buffer read from disk into cache
! Buffer written from cache to disk
! Deferred writeback from cache to disk
! Cross process hit count.
! Count of times GBLBUFQUO limit was hit.
! Force quadword alignment

```



```

1808 0 !
1809 0 literal TRC$C_BID = 18;
1810 0 literal TRC$K_BLN = 64;
1811 0 literal TRC$C_BLN = 64;
1812 0 literal TRC$S_TRCDEF = 64;
1813 0 macro TRC$L_FCNK = 0,0,32,0 %;
1814 0 macro TRC$L_BLNK = 4,0,32,0 %;
1815 0 macro TRC$B_BID = 8,0,8,0 %;
1816 0 macro TRC$B_BLN = 9,0,8,0 %;
1817 0 macro TRC$W_FUNCTION = 10,0,16,0 %;
1818 0 macro TRC$L_STRUCTURE = 12,0,32,0 %;
1819 0 macro TRC$W_PID = 16,0,16,0 %;
1820 0 macro TRC$W_SEQNUM = 18,0,16,0 %;
1821 0 macro TRC$L_VBN = 20,0,32,0 %;
1822 0 macro TRC$L_RETURN1 = 24,0,32,0 %;
1823 0 macro TRC$L_RETURN2 = 28,0,32,0 %;
1824 0 macro TRC$L_ARGS = 32,0,0,0 %;
1825 0 literal TRC$S_ARGS = 32;
1826 0 macro TRC$L_ARG_FLG = 32,0,32,0 %;
1827 0 macro TRC$L_BDB_ADDR = 36,0,32,0 %;
1828 0 macro TRC$W_BDB_USERS = 40,0,16,0 %;
1829 0 macro TRC$W_BDB_BUFF = 42,0,16,0 %;
1830 0 macro TRC$B_BDB_CACHE = 44,0,8,0 %;
1831 0 macro TRC$B_BDB_FLAGS = 45,0,8,0 %;
1832 0 macro TRC$L_BDB_SEQ = 46,0,32,0 %;
1833 0 macro TRC$B_BLB_MODE = 50,0,8,0 %;
1834 0 macro TRC$B_BLB_FLAGS = 51,0,8,0 %;
1835 0 macro TRC$L_BLB_ADDR = 52,0,32,0 %;
1836 0 macro TRC$L_BLB_LOCK = 56,0,32,0 %;
1837 0 macro TRC$L_BLB_SEQ = 60,0,32,0 %;
1838 0 ! maintain quad alignment on header
1839 0
1840 0 *** MODULE $GBDDEF ***
1841 0
1842 0 GBD structure definitions
1843 0
1844 0 Global Buffer Descriptor (GBD)
1845 0
1846 0 There is a single GBD for every buffer in a global buffer
1847 0 section (used only with shared files). The GBD's themselves
1848 0 are in the section also and linked from a queue header in
1849 0 the Global Buffer Header (GBH).
1850 0
1851 0 *** WARNING - THIS STRUCTURE MUST BE QUADWORD ALIGNED ***
1852 0
1853 0 ! Block ID code for GBD
1854 0 ! Length of Global Buffer Descriptor structure.
1855 0 ! Length of Global Buffer Descriptor structure.
1856 0
1857 0 ! Forward link - Note: This is a self relative queue
1858 0 ! Back link
1859 0 ! Block ID
1860 0 ! Block length of GBD
1861 0 ! Buffer status flags
1862 0 ! Buffer is valid.
1863 0 ! Cache value of this bucket
1864 0 macro GBD$B_CACHE_VAL = 11,0,8,0 %;

```

Trace block code
NOTE: should be quadwords multiple to
NOTE: should be quadwords multiple to

Trace block forward link
Trace block back link
Block ID
Length of block in longwords
Function code (see GBH definitions)
Ifab/irab address.
Process ID
Sequence number.
VBN requested.
Address of caller.
Caller's caller.

Function specific arguments
Argument flags (R3).
BDB address.
Use count from BDB.
BDB buffer ID.
BDB cache value.
Status flags from BDB.
Sequence number from BDB.
Mode held in BLB.
Flags from BLB.
Address of BLB.
Lock ID from BLB.
Sequence number from BLB.


```

1865 0 macro GBD$$_VBN = 12,0,32,0 %;
1866 0 macro GBD$$_VBNSEQNUM = 16,0,32,0 %;
1867 0 macro GBD$$_LOCK_ID = 20,0,32,0 %;
1868 0 macro GBD$$_NUMB = 24,0,16,0 %;
1869 0 macro GBD$$_SIZE = 26,0,16,0 %;
1870 0 macro GBD$$_REL_ADDR = 28,0,32,0 %;
1871 0 macro GBD$$_USECNT = 32,0,16,0 %;
1872 0 macro GBD$$_REHIT_RD = 34,0,8,0 %;
1873 0 macro GBD$$_REHIT_LK = 35,0,8,0 %;

```

```

! VBN of bucket the buffer describes
! VBN sequence number validity check
! Lock ID of system lock.
! Number of bytes in use
! Size of buffer in bytes
! Address of buffer relative to GBH
! Accessor count for bucket
! Rehit by same process count.
! Rehit by same locker process.

```

```

1875 0 !*** MODULE $BLBDEF ***

```

```

1876 0 !
1877 0 ! BLB field definitions

```

```

1878 0 !
1879 0 ! Bucket Lock Block (BLB)

```

```

1880 0 !
1881 0 ! The BLB contains the argument list for the SYS$ENQ system service
1882 0 ! as well a pointer to the BDB it relates to and other status.
1883 0 !

```

```

1884 0 literal BLB$$_BID = 16;
1885 0 literal BLB$$_LOCK = 1;
1886 0 literal BLB$$_NOWAIT = 2;
1887 0 literal BLB$$_NOREAD = 4;
1888 0 literal BLB$$_NOBUFFER = 8;
1889 0 literal BLB$$_IOLOCK = 16;
1890 0 literal BLB$$_DFW = 32;
1891 0 literal BLB$$_WRITEBACK = 64;
1892 0 literal BLB$$_BLN = 56;
1893 0 literal BLB$$_BLN = 56;
1894 0 literal BLB$$_BLBDEF = 56;
1895 0 macro BLB$$_FNK = 0,0,32,0 %;
1896 0 macro BLB$$_BLNK = 4,0,32,0 %;
1897 0 macro BLB$$_BID = 8,0,8,0 %;
1898 0 macro BLB$$_BLN = 9,0,8,0 %;
1899 0 macro BLB$$_BLBFLGS = 10,0,8,0 %;
1900 0 macro BLB$$_LOCK = 10,0,1,0 %;
1901 0 macro BLB$$_NOWAIT = 10,1,1,0 %;
1902 0 macro BLB$$_NOREAD = 10,2,1,0 %;
1903 0 macro BLB$$_NOBUFFER = 10,3,1,0 %;
1904 0 macro BLB$$_IOLOCK = 10,4,1,0 %;
1905 0 macro BLB$$_DFW = 10,5,1,0 %;
1906 0 macro BLB$$_WRITEBACK = 10,6,1,0 %;
1907 0 macro BLB$$_MODEHELD = 11,0,8,0 %;
1908 0 macro BLB$$_BDB_ADDR = 12,0,32,0 %;
1909 0 macro BLB$$_OWNER = 16,0,32,0 %;
1910 0 macro BLB$$_VBN = 20,0,32,0 %;
1911 0 macro BLB$$_RESDESC = 24,0,0,0 %;
1912 0 literal BLB$$_RESDESC = 8;
1913 0 macro BLB$$_LRSTS = 32,0,16,0 %;
1914 0 macro BLB$$_LOCK_ID = 36,0,32,0 %;
1915 0 macro BLB$$_VALBLK = 40,0,0,0 %;
1916 0 literal BLB$$_VALBLK = 16;
1917 0 macro BLB$$_VALSEQNO = 40,0,32,0 %;

```

```

! BLB code

```

```

! Length of BLB
! Length of BLB

```

```

! Link to next BLB
! Back link
! Block ID
! Block length
! Control flags for BLB
! Corresponds to CSH$$_LOCK
! Same as CSH$$_NOWAIT
! Same as CSH$$_NOREAD
! Same as CSH$$_NOBUFFER
! Lock mode for read/write
! This is lock for deferred write buffer
! The associated buffer must be written back
! Mode of current lock held.
! BDB for which this lock is held
! Address of stream owning this lock
! VBN of bucket lock (resource name)

```

```

! Resource name descriptor
! Lock status word
! Lock ID

```

```

! Lock value block
! Sequence number part of value block

```

```

1919 0 !*** MODULE $RJBDEF ***

```

```

1920 0 !
1921 0 ! RJB Definitions

```



```

1922 0
1923 0
1924 0
1925 0
1926 0
1927 0
1928 0
1929 0
1930 0
1931 0
1932 0
1933 0
1934 0
1935 0
1936 0
1937 0
1938 0
1939 0
1940 0
1941 0
1942 0
1943 0
1944 0
1945 0
1946 0
1947 0
1948 0
1949 0
1950 0
1951 0
1952 0
1953 0
1954 0
1955 0
1956 0
1957 0
1958 0
1959 0
1960 0
1961 0
1962 0
1963 0
1964 0
1965 0
1966 0
1967 0
1968 0
1969 0
1970 0
1971 0
1972 0
1973 0
1974 0
1975 0
1976 0
1977 0
1978 0

```

RMS Journaling Block (RJB)

This block contains the necessary control information to keep track of the state of journaling on this file

```

literal RJB$C_BID = 22;
literal RJB$K_BLN = 12;
literal RJB$C_BLN = 12;
literal RJB$M_RU = 1;
literal RJB$M_BI = 2;
literal RJB$M_AI = 4;
literal RJB$M_AT = 8;
literal RJB$M_OPEN = 16;
literal RJB$S_RJBDEF = 12;
macro RJB$Q_CHAN = 0,0,0,0 %;
literal RJB$S_CHAN = 8;
macro RJB$W_RUCHAN = 0,0,16,0 %;
macro RJB$W_BICHAN = 2,0,16,0 %;
macro RJB$W_AICHAN = 4,0,16,0 %;
macro RJB$W_ATCHAN = 6,0,16,0 %;
macro RJB$B_BID = 8,0,8,0 %;
macro RJB$B_BLN = 9,0,8,0 %;
macro RJB$W_FLAGS = 10,0,16,0 %;
macro RJB$V_RU = 10,0,1,0 %;
macro RJB$V_BI = 10,1,1,0 %;
macro RJB$V_AI = 10,2,1,0 %;
macro RJB$V_AT = 10,3,1,0 %;
macro RJB$V_OPEN = 10,4,1,0 %;

```

! Length of RJB
! Length of RJB

Channel Block
channel for recovery unit journal
channel for before image journal
channel for after image journal
channel for audit trail journal

Block Id
Block Length
Flags word
Set to indicate RU channel open
Set to indicate BI channel open
Set to indicate AI channel open
Set to indicate AT channel open
Indicates \$OPEN mapping entry written

*** MODULE \$MJBDEF ***

MJB field definitions

Miscellaneous Journaling Buffer

The MJB is used for writing miscellaneous journal entries, for example, extend entries or audit-trail entries.

```

literal MJB$C_BID = 24;
literal MJB$M_INIT = 1;
literal MJB$M_FORCE = 2;
literal MJB$M_FILE = 4;
literal MJB$M_SYNCH_SHARE = 8;
literal MJB$K_BLN = 32;
literal MJB$C_BLN = 32;
literal MJB$S_MJBDEF = 32;
macro MJB$B_BID = 8,0,8,0 %;
macro MJB$B_BLN = 9,0,8,0 %;
macro MJB$W_FLAGS = 10,0,16,0 %;
macro MJB$V_INIT = 10,0,1,0 %;
macro MJB$V_FORCE = 10,1,1,0 %;
macro MJB$V_FILE = 10,2,1,0 %;
macro MJB$V_SYNCH_SHARE = 10,3,1,0 %;
! STALL
! and not buffered by CJF (input to WRITE_MJB)
macro MJB$B_JNL = 12,0,8,0 %;

```

block id
block length in longwords
flags
set if RJR overhead is initialized
set if RJR is to be written thru to journal
set if file operation to journal
set if file lock can't be released during

! set to CJF\$_'jnl type' as input to WRITE_MJB

N 3
15-Sep-1984 22:56:58
15-Sep-1984 22:56:57

VAX-11 Bliss-32 V4.0-742
_S255SDUA28:[RMS.OBJ]RMSINTDEF.R32;1

Page 40
(9)

```
1979 0 macro MJB$Q_DESC = 16,0,0,0 %;
1980 0 literal MJB$S_DESC = 8;
1981 0 macro MJB$W_SIZE = 16,0,16,0 %;
1982 0 macro MJB$S_POINTER = 20,0,32,0 %;
1983 0 macro MJB$Q_IOSB = 24,0,0,0 %;
1984 0 literal MJB$S_IOSB = 8;
1985 0 macro MJB$T_RJR = 32,0,0,0 %;
1986 0
1987 0
1988 0
1989 0
1990 0
1991 0
1992 0
1993 0
1994 0
1995 0
1996 0
1997 0
1998 0
1999 0
2000 0
2001 0
2002 0
2003 0
2004 0
2005 0
2006 0
2007 0
2008 0
2009 0
2010 0
2011 0
2012 0
2013 0
2014 0
2015 0
2016 0
2017 0
2018 0
2019 0
2020 0
2021 0
2022 0
2023 0
2024 0
2025 0
2026 0
2027 0
2028 0
2029 0
2030 0
2031 0
2032 0
2033 0
2034 0
2035 0
```

! RJR descriptor used in \$WRITEJNL service
! size of RJR to write
! pointer to RJR
! IOSB to use in \$WRITEJNL
! the journal record begins here

```
*****
*
* Copyright (c) 1982, 1983
* by DIGITAL Equipment Corporation, Maynard, Mass.
*
* This software is furnished under a license and may be used and copied
* only in accordance with the terms of such license and with the
* inclusion of the above copyright notice. This software or any other
* copies thereof may not be provided or otherwise made available to any
* other person. No title to and ownership of the software is hereby
* transferred.
*
* The information in this software is subject to change without notice
* and should not be construed as a commitment by DIGITAL Equipment
* Corporation.
*
* DIGITAL assumes no responsibility for the use or reliability of its
* software on equipment which is not supplied by DIGITAL.
*
```

```
*****
*****
Created 15-SEP-1984 22:54:20 by VAX-11 SDL V2.0 Source: 15-SEP-1984 22:49:17 _S255SDUA28:[RMS.SRC]RMSFWAD
*****
```

*** MODULE \$FWADEF ***

++

Flags

--

```
literal FWASM_DUPOK = 1;
literal FWASM_NOCOPY = 2;
literal FWASM_SL_PASS = 4;
literal FWASM_RLF_PASS = 8;
literal FWASM_FNA_PASS = 16;
literal FWASM_NAM_DVI = 32;
literal FWASM_EXP_NODE = 64;
literal FWASM_VERSION = 2048;
literal FWASM_TYPE = 4096;
literal FWASM_NAME = 8192;
literal FWASM_DIR = 16384;
literal FWASM_DEVICE = 32768;
literal FWASM_EXP_VER = 65536;
literal FWASM_EXP_TYPE = 131072;
literal FWASM_EXP_NAME = 262144;
literal FWASM_WC_VER = 524288;
literal FWASM_WC_TYPE = 1048576;
literal FWASM_WC_NAME = 2097152;
```



```

2036 0 literal FWASM_EXP_DIR = 4194304;
2037 0 literal FWASM_EXP_DEV = 8388608;
2038 0 literal FWASM_WILDCARD = 16777216;
2039 0 literal FWASM_NODE = 33554432;
2040 0 literal FWASM_QUOTED = 67108864;
2041 0 literal FWASM_GRPMBR = 134217728;
2042 0 literal FWASM_WILD_DIR = 268435456;
2043 0 literal FWASM_DIR_EVLS = -536870912;
2044 0 literal FWASC_ALL = 248;
2045 0
2046 0 constant for all flags that vary per parsing pass
2047 0
2048 0 literal FWASC_ALLPASS = 25;
2049 0 ++
2050 0
2051 0 Misc. Fields
2052 0
2053 0 --
2054 0 literal FWASC_BID = 40; ! bid of fwa
2055 0 literal FWASC_MAXNODNAM = 6; ! max node name size
2056 0 literal FWASC_MAXLNDNAM = 15; ! max logical node name size
2057 0 literal FWASC_MAXNODLST = 127; ! max node spec list size (concatenated node specs)
2058 0
2059 0 device name descriptor
2060 0
2061 0 literal FWASC_MAXDEVICE = 255; ! max device name size
2062 0 literal FWASC_MAXCDIR = 8; ! max number of concealed directories
2063 0 literal FWASC_MAXSUBDIR = 7; ! max number of sub directories
2064 0 literal FWASC_MAXDIRLEN = 255; ! max size of total directory spec
2065 0 should be: top + subdir 39 * 8
2066 0 dots between 7
2067 0 delimiters 2
2068 0 -----
2069 0 total 321
2070 0
2071 0 The filename, filetype and fileversion descriptors MUST be contiguous
2072 0
2073 0 file name descriptor
2074 0
2075 0 literal FWASC_MAXNAME = 39; ! max file name size
2076 0 literal FWASC_MAXQUOTED = 255; ! max quoted string size
2077 0
2078 0 file type descriptor
2079 0
2080 0 literal FWASC_MAXTYPE = 39; ! max file type size
2081 0
2082 0 file version number descriptor
2083 0
2084 0 literal FWASC_MAXVER = 6; ! maximum version
2085 0 literal FWASC_MAXRNS = 86; ! max resultant name string size
2086 0 literal FWASC_STATBLK = 10; ! define length of statistics block
2087 0 literal FWASK_BLN_FWA = 500; ! length of fwa
2088 0 literal FWASC_BLN_FWA = 500; ! length of fwa
2089 0 literal FWASC_MAXSUBNOD = 7; ! max number of secondary (sub) node specs
2090 0 ++
2091 0
2092 0 buffers for parsed filename elements

```



```

2093 0  |
2094 0  |  --
2095 0  | literal FWASC_FIBLEN = 76;      | fib buffer size
2096 0  | literal FWASC_DIRBUFSIZ = 39;  | size of each directory buffer
2097 0  |
2098 0  |   rooted directory name buffers
2099 0  |
2100 0  |   NOTE: These buffers must be contiguous
2101 0  |
2102 0  | literal FWASK_BLN_BUF = 2364;  | length of fwa and buffers
2103 0  | literal FWASC_BLN_BUF = 2364;  | length of fwa and buffers
2104 0  | literal FWASK_BLN = 2364;      | length of fwa and buffers
2105 0  | literal FWASC_BLN = 2364;      | length of fwa and buffers
2106 0  | literal FWASS_FWDEF = 2364;
2107 0  | macro FWASQ_FLAGS = 0,0,0,0 %;
2108 0  | literal FWASS_FLAGS = 8;      | various parse status flags
2109 0  | macro FWASB_PASSFLGS = 0,0,8,0 %; | flags for pass only
2110 0  | macro FWASB_FLDFLGS = 1,0,8,0 %; | flags for fields seen
2111 0  | macro FWASB_WILDFLGS = 2,0,8,0 %; | flags for wild cards
2112 0  | macro FWASB_PARSEFLGS = 3,0,8,0 %; | flags for parse results
2113 0  | macro FWASB_DIRFLGS = 4,0,8,0 %; | flags primarily for directory spec
2114 0  | macro FWASB_DIRWCFLGS = 5,0,8,0 %; | directory wild flags
2115 0  | macro FWASB_LNFLGS = 6,0,8,0 %; | logical name flag byte
2116 0  | macro FWASB_SLFLGS = 7,0,8,0 %; | search list + rooted directory flags
2117 0  |
2118 0  |   flags for pass
2119 0  |
2120 0  | macro FWASV_DUPOK = 0,0,1,0 %; | discard duplicate element
2121 0  | macro FWASV_NOCOPY = 0,1,1,0 %; | do not copy this field
2122 0  | macro FWASV_SL_PASS = 0,2,1,0 %; | search list pass
2123 0  | macro FWASV_RLF_PASS = 0,3,1,0 %; | set if applying related file defaults
2124 0  | macro FWASV_FNA_PASS = 0,4,1,0 %; | set if primary name string parse pass
2125 0  | macro FWASV_NAM_DVI = 0,5,1,0 %; | set if open by name block
2126 0  | macro FWASV_EXP_NODE = 0,6,1,0 %; | explicit node has been seen, null or normal
2127 0  |
2128 0  |   flags for fields seen
2129 0  |
2130 0  | macro FWASV_VERSION = 0,11,1,0 %; | set if version seen
2131 0  | macro FWASV_TYPE = 0,12,1,0 %; | set if type seen
2132 0  | macro FWASV_NAME = 0,13,1,0 %; | set if name seen
2133 0  | macro FWASV_DIR = 0,14,1,0 %; | set if directory spec seen
2134 0  | macro FWASV_DEVICE = 0,15,1,0 %; | set if device seen
2135 0  |
2136 0  |   flags for wild cards
2137 0  |
2138 0  | macro FWASV_EXP_VER = 0,16,1,0 %; | set if explicit version
2139 0  | macro FWASV_EXP_TYPE = 0,17,1,0 %; | set if explicit type
2140 0  | macro FWASV_EXP_NAME = 0,18,1,0 %; | set if explicit name
2141 0  | macro FWASV_WC_VER = 0,19,1,0 %; | set if wildcard (*) version
2142 0  | macro FWASV_WC_TYPE = 0,20,1,0 %; | " type
2143 0  | macro FWASV_WC_NAME = 0,21,1,0 %; | " name
2144 0  | macro FWASV_EXP_DIR = 0,22,1,0 %; | set if explicit directory
2145 0  | macro FWASV_EXP_DEV = 0,23,1,0 %; | set if explicit device
2146 0  |
2147 0  |   flags for parse results
2148 0  |
2149 0  | macro FWASV_WILDCARD = 0,24,1,0 %; | set if any wildcard seen

```



```

2150 0 macro FWASV_NODE = 0,25,1,0 %;      ! set if node name seen
2151 0 macro FWASV_QUOTED = 0,26,1,0 %;    ! set if quoted string seen
2152 0 macro FWASV_GRPMBR = 0,27,1,0 %;    ! set if directory in [grp,mbr] format
2153 0 macro FWASV_WILD_DIR = 0,28,1,0 %;   ! inclusive or of directory wild cards
2154 0 macro FWASV_DIR_LVL = 0,29,3,0 %;    !
2155 0 literal FWASV_DIR_LVL = 3;           ! of directory sublevels (0 = ufd only)
2156 0 (valid only if node set and no fldflgs)
2157 0
2158 0 flags primarily for directory spec
2159 0
2160 0 macro FWASV_DIR1 = 4,0,1,0 %;          ! ufd level directory or group seen
2161 0 macro FWASV_DIR2 = 4,1,1,0 %;          ! sfd level 1 directory or member seen
2162 0
2163 0 directory wild flags
2164 0
2165 0 macro FWASV_WILD_UFD = 4,8,1,0 %;      ! the dir1 spec was a wild card
2166 0 macro FWASV_WILD_SFD1 = 4,9,1,0 %;    ! the dir2 spec was a wild card
2167 0 macro FWASV_WILD_GRP = 4,8,1,0 %;     ! the grp spec contained a wild card
2168 0 macro FWASV_WILD_MBR = 4,9,1,0 %;     ! the mbr spec contained a wild card
2169 0
2170 0 logical name flag and miscellaneous byte
2171 0
2172 0 macro FWASV_LOGNAME = 4,16,1,0 %;       ! a logical name has been seen this pass
2173 0 (note: this byte is saved as context
2174 0 when processing [.dir-list] format)
2175 0 macro FWASV_OBJTYPE = 4,17,1,0 %;      ! set if quoted string is of the
2176 0 "objectType=..." form
2177 0 (valid only if quoted set)
2178 0 macro FWASV_NETSTR = 4,18,1,0 %;       ! set if quoted string is of the
2179 0 "objectType=taskname/..." form
2180 0 (valid only if quoted and objtype set)
2181 0 macro FWASV_DEV_UNDER = 4,19,1,0 %;     ! device name was prefixed with an underscore
2182 0 macro FWASV_FILEFOUND = 4,20,1,0 %;    ! true if at least one file found by search
2183 0 macro FWASV_REMRESULT = 4,21,1,0 %;    ! use resultant string returned by fal
2184 0 macro FWASV_SYNTAX_CHK = 4,22,1,0 %;   ! syntax-only checking is requested (NAMS_V_SYNCHK set)
2185 0
2186 0 search list and rooted directory flag byte
2187 0
2188 0 macro FWASV_SLPRESENT = 4,24,1,0 %;      ! search list present
2189 0 macro FWASV_CONCEAL_DEV = 4,25,1,0 %;   ! concealed device present
2190 0 macro FWASV_ROOT_DIR = 4,26,1,0 %;     ! root directory present
2191 0 macro FWASV_DFLT_MFD = 4,27,1,0 %;     ! default MFD string inserted, due to [-]
2192 0 macro FWASV_EXP_ROOT = 4,28,1,0 %;     ! explicit root directory
2193 0
2194 0 Value for all filename elements except node
2195 0
2196 0 macro FWASB_BID = 8,0,8,0 %;             ! bid
2197 0 macro FWASB_BLN = 9,0,8,0 %;           ! bln
2198 0 macro FWASB_DIRTERM = 10,0,8,0 %;      ! directory spec terminator (']' or '>')
2199 0 macro FWASB_ROOTERM = 11,0,8,0 %;      ! root directory spec terminator (']' or '>')
2200 0 macro FWASL_ESCSTRING = 12,0,32,0 %;   ! escape equivalence string
2201 0 macro FWASB_ESCFLG = 12,0,8,0 %;       ! set to the char <esc> if an escape string
2202 0 ! seen, zero otherwise
2203 0 macro FWASB_ESCTYP = 13,0,8,0 %;        ! escape 'type' byte
2204 0 macro FWASB_ESCIFI = 14,0,16,0 %;      ! escape ifi value
2205 0 macro FWASQ_FIB = 16,0,0,0 %;          !
2206 0 literal FWASB_FIB = 8;                 ! fib descriptor

```



```

2207 0 macro FWASL_DEVBUFSIZ = 24,0,32,0 %; : device buffer size
2208 0 macro FWASL_DEV CLASS = 28,0,32,0 %; : device class
2209 0 macro FWASL_REC SIZE = 32,0,32,0 %; : blocked record size
2210 0 macro FWASL_UNIT = 36,0,32,0 %; : device unit number
2211 0 macro FWASL_UIC = 40,0,32,0 %; : file owner uic
2212 0 macro FWASW_PRO = 44,0,16,0 %; : file protection word
2213 0 macro FWASB_DIRLEN = 46,0,8,0 %; : overall directory spec length
2214 0 macro FWASB_SUBNODCNT = 47,0,8,0 %; : number of secondary (sub) node specs found
2215 0 macro FWASL_DIRBDB = 48,0,32,0 %; : address of directory file bdb
2216 0 macro FWASL_LOOKUP = 52,0,32,0 %; : address of new directory cache node
2217 0 macro FWASL_DEVNODADR = 56,0,32,0 %; : address of device directory cache node
2218 0 macro FWASQ_DIR = 60,0,0,0 %; :
2219 0 literal FWASS_DIR = 8; : directory name scratch buffer
2220 0 macro FWASL_UCHAR = 68,0,32,0 %; : user characteristics longword
2221 0 macro FWASW_UCHAR = 68,0,16,0 %; :
2222 0 macro FWASL_FWA_PTR = 72,0,32,0 %; : pointer to second fwa if any ($RENAME)
2223 0 macro FWASL_SWB_PTR = 76,0,32,0 %; : pointer to swb
2224 0 macro FWASL_BUF_PTR = 80,0,32,0 %; : address of temporary buffer
2225 0 macro FWASL_IMPURE AREA = 84,0,32,0 %; : saved R11 (rm$xpfn only)
2226 0 macro FWASL_ATR_WORK = 88,0,32,0 %; : pointer to work area for ACP attributes
2227 0 : (zero if one not currently allocated)
2228 0 ++
2229 0
2230 0 Logical name and search list fields
2231 0
2232 0 --
2233 0
2234 0 Item list block for logical name services
2235 0
2236 0 macro FWAST_ITMLST = 92,0,0,0 %; :
2237 0 literal FWASS_ITMLST = 64; : logical name item list
2238 0 macro FWAST_ITM_INDEX = 92,0,0,0 %; :
2239 0 literal FWASS_ITM_INDEX = 12; : index
2240 0 macro FWAST_ITM_ATTR = 104,0,0,0 %; :
2241 0 literal FWASS_ITM_ATTR = 12; : attributes
2242 0 macro FWAST_ITM_STRING = 116,0,0,0 %; :
2243 0 literal FWASS_ITM_STRING = 12; : string
2244 0 macro FWAST_ITM_MAX_INDEX = 128,0,0,0 %; :
2245 0 literal FWASS_ITM_MAX_INDEX = 12; : max index
2246 0 macro FWASL_ITM_END = 140,0,32,0 %; : terminating longword
2247 0
2248 0 Logical name translation fields
2249 0
2250 0 macro FWASB_BUF FLG = 156,0,8,0 %; : flag for which translation buffer is in use
2251 0 ! (0 = buf2 in use, -1 = buf1 in use)
2252 0 macro FWASB_XLT MODE = 157,0,8,0 %; : mode of translation on input to $TRNLNM
2253 0 ! mode of equivalence string on output from $TRNLNM
2254 0 macro FWASW_XLT SIZE = 158,0,16,0 %; : length of equivalence string
2255 0 macro FWASL_XLT BUFF1 = 160,0,32,0 %; : primary translation buffer descriptor
2256 0 macro FWASL_XLT BUFF2 = 164,0,32,0 %; : secondary translation buffer descriptor
2257 0
2258 0 SLBH and SLB pointers
2259 0
2260 0 macro FWASL_SLBH_PTR = 168,0,32,0 %; : current SLB list
2261 0 macro FWASL_SLB_PTR = 172,0,32,0 %; : current SLB list
2262 0 macro FWASL_SLBH_FLINK = 176,0,32,0 %; : SLBH que fwd link
2263 0 macro FWASL_SLBH_BLINK = 180,0,32,0 %; : SLBH que back link

```


2264 0
2265 0
2266 0
2267 0
2268 0
2269 0
2270 0
2271 0
2272 0
2273 0
2274 0
2275 0
2276 0
2277 0
2278 0
2279 0
2280 0
2281 0
2282 0
2283 0
2284 0
2285 0
2286 0
2287 0
2288 0
2289 0
2290 0
2291 0
2292 0
2293 0
2294 0
2295 0
2296 0
2297 0
2298 0
2299 0
2300 0
2301 0
2302 0
2303 0
2304 0
2305 0
2306 0
2307 0
2308 0
2309 0
2310 0
2311 0
2312 0
2313 0
2314 0
2315 0
2316 0
2317 0
2318 0
2319 0
2320 0

Fake SLB - NOTE: This MUST be the size of SLB\$C_BLN
The field FWASB_LEVEL must be at the same offset
as SLB\$Q_LEVEL would be. (It sounds like a real
hack but it works very nicely)

macro FWASL SLB = 184,0,0,0 %;
literal FWASS_SLB = 24; ! space for SLB\$C_BLN
macro FWASB_LEVEL = 195,0,8,0 %; ! recursion level

Logical name descriptor
macro FWASQ_LOGNAM = 208,0,0,0 %;
literal FWASS_LOGNAM = 8; ! logical name descriptor
++

descriptors for parsed filename elements

The descriptors are defined as:

flags	length
address	

The flags are defined by FSCB\$V_flag in \$FSCBDEF

--
macro FWASQ_NODE = 216,0,0,0 %;
literal FWASS_NODE = 8; ! node name (actually node spec list) descriptor
! (the associated buffer is fwa\$t_nodebuf)

macro FWASQ_DEVICE = 224,0,0,0 %;
literal FWASS_DEVICE = 8; ! device name descriptor
macro FWASQ_CONCEAL_DEV = 232,0,0,0 %;
literal FWASS_CONCEAL_DEV = 8; ! concealed device descriptor

directory name descriptors NOTE: The two sets of directory
descriptors must be contiguous
or RM\$SETDID will break

macro FWASQ_CDIR1 = 240,0,0,0 %;
literal FWASS_CDIR1 = 8; ! concealed top directory descriptors
macro FWASQ_CDIR2 = 248,0,0,0 %;
literal FWASS_CDIR2 = 8; ! concealed subdirectory 1
macro FWASQ_CDIR3 = 256,0,0,0 %;
literal FWASS_CDIR3 = 8; ! " " 2
macro FWASQ_CDIR4 = 264,0,0,0 %;
literal FWASS_CDIR4 = 8; ! " " 3
macro FWASQ_CDIR5 = 272,0,0,0 %;
literal FWASS_CDIR5 = 8; ! " " 4
macro FWASQ_CDIR6 = 280,0,0,0 %;
literal FWASS_CDIR6 = 8; ! " " 5
macro FWASQ_CDIR7 = 288,0,0,0 %;
literal FWASS_CDIR7 = 8; ! " " 6


```

2321 0 macro FWASQ_CDIR8 = 296,0,0,0 %;
2322 0 literal FWASS_CDIR8 = 8;
2323 0 macro FWASQ_DIR1 = 304,0,0,0 %;
2324 0 literal FWASS_DIR1 = 8;
2325 0 macro FWASQ_DIR2 = 312,0,0,0 %;
2326 0 literal FWASS_DIR2 = 8;
2327 0 macro FWASQ_DIR3 = 320,0,0,0 %;
2328 0 literal FWASS_DIR3 = 8;
2329 0 macro FWASQ_DIR4 = 328,0,0,0 %;
2330 0 literal FWASS_DIR4 = 8;
2331 0 macro FWASQ_DIR5 = 336,0,0,0 %;
2332 0 literal FWASS_DIR5 = 8;
2333 0 macro FWASQ_DIR6 = 344,0,0,0 %;
2334 0 literal FWASS_DIR6 = 8;
2335 0 macro FWASQ_DIR7 = 352,0,0,0 %;
2336 0 literal FWASS_DIR7 = 8;
2337 0 macro FWASQ_DIR8 = 360,0,0,0 %;
2338 0 literal FWASS_DIR8 = 8;
2339 0 macro FWASQ_NAME = 368,0,0,0 %;
2340 0 literal FWASS_NAME = 8;
2341 0 macro FWASQ_QUOTED = 368,0,0,0 %;
2342 0 literal FWASS_QUOTED = 8;
2343 0 macro FWASQ_TYPE = 376,0,0,0 %;
2344 0 literal FWASS_TYPE = 8;
2345 0 macro FWASQ_VERSION = 384,0,0,0 %;
2346 0 literal FWASS_VERSION = 8;
2347 0 macro FWASQ_RNS = 392,0,0,0 %;
2348 0 literal FWASS_RNS = 8;
2349 0 macro FWASQ_SHRFIL = 400,0,0,0 %;
2350 0 literal FWASS_SHRFIL = 8;
2351 0 macro FWASQ_SHRFIL_LCK = 408,0,0,0 %;
2352 0 literal FWASS_SHRFIL_LCK = 8;
2353 0 macro FWASQ_AS_SHRFIL = 416,0,0,0 %;
2354 0 literal FWASS_AS_SHRFIL = 8;
2355 0 macro FWASQ_STATBLK = 424,0,0,0 %;
2356 0 literal FWASS_STATBLK = 10;
2357 0 macro FWASL_SBN = 424,0,32,0 %;
2358 0 macro FWASL_HBK = 428,0,32,0 %;
2359 0
2360 0 node descriptors
2361 0
2362 0 macro FWASQ_NODE1 = 436,0,0,0 %;
2363 0 literal FWASS_NODE1 = 8;
2364 0 ! (the associated buffer is fwaSt_nodebuf)
2365 0 macro FWASQ_NODE2 = 444,0,0,0 %;
2366 0 literal FWASS_NODE2 = 8;
2367 0 macro FWASQ_NODE3 = 452,0,0,0 %;
2368 0 literal FWASS_NODE3 = 8;
2369 0 macro FWASQ_NODE4 = 460,0,0,0 %;
2370 0 literal FWASS_NODE4 = 8;
2371 0 macro FWASQ_NODE5 = 468,0,0,0 %;
2372 0 literal FWASS_NODE5 = 8;
2373 0 macro FWASQ_NODE6 = 476,0,0,0 %;
2374 0 literal FWASS_NODE6 = 8;
2375 0 macro FWASQ_NODE7 = 484,0,0,0 %;
2376 0 literal FWASS_NODE7 = 8;
2377 0 macro FWASQ_NODE8 = 492,0,0,0 %;

```

! " " 7
! top level directory descriptors
! subdirectory 1
! " 2
! " 3
! " 4
! " 5
! " 6
! " 7
! file name descriptor
! quoted string descriptor
! file type descriptor
! file version descriptor
! resultant name string descriptor
! shared file device descriptor (readable form)
! shared file device descriptor (unreadable form - used for lock name)
! secondary device descriptor (readable form)
! starting lbn if contiguous
! high vbn

! primary node spec descriptor
! secondary (sub) node spec descriptors (1-7)
! note: bytes 2-3 of each of these descriptors
! contains the flags word that is output
! from nextfld subroutine in rm0xpfn
! note: fwaSq_node1 thru 'fwaSq_node8'
! describe the same string as does

H 4
15-Sep-1984 22:56:58
15-Sep-1984 22:56:57

VAX-11 Bliss-32 V4.0-742
_S255SDUA28:[RMS.OBJ]RMSINTDEF.R32;1 Page 47
(9)

```
2378 0 literal FWASS NODE8 = 8; ! fwa$q_node
2379 0 macro FFAST FIBBUF = 500,0,0,0 %;
2380 0 literal FWASS FIBBUF = 76; ! fib buffer
2381 0 macro FFAST RNM_FID = 576,0,0,0 %;
2382 0 literal FWASS_RNM_FID = 6; ! saved fid for rename directory check
2383 0
2384 0 directory name buffers
2385 0
2386 0 NOTE: These buffers must be contiguous
2387 0
2388 0 macro FFAST DIR1BUF = 582,0,0,0 %;
2389 0 literal FWASS DIR1BUF = 39; ! ufd level (or group)
2390 0 macro FFAST DIR2BUF = 621,0,0,0 %;
2391 0 literal FWASS DIR2BUF = 39; ! 1st sfd level (or member)
2392 0 macro FFAST DIR3BUF = 660,0,0,0 %;
2393 0 literal FWASS DIR3BUF = 39; ! subdirectory 2
2394 0 macro FFAST DIR4BUF = 699,0,0,0 %;
2395 0 literal FWASS DIR4BUF = 39; ! subdirectory 3
2396 0 macro FFAST DIR5BUF = 738,0,0,0 %;
2397 0 literal FWASS DIR5BUF = 39; ! subdirectory 4
2398 0 macro FFAST DIR6BUF = 777,0,0,0 %;
2399 0 literal FWASS DIR6BUF = 39; ! subdirectory 5
2400 0 macro FFAST DIR7BUF = 816,0,0,0 %;
2401 0 literal FWASS DIR7BUF = 39; ! subdirectory 6
2402 0 macro FFAST DIR8BUF = 855,0,0,0 %;
2403 0 literal FWASS DIR8BUF = 39; ! subdirectory 7
2404 0 macro FFAST CDIR1BUF = 894,0,0,0 %;
2405 0 literal FWASS CDIR1BUF = 39; ! ufd level (or group)
2406 0 macro FFAST CDIR2BUF = 933,0,0,0 %;
2407 0 literal FWASS CDIR2BUF = 39; ! 1st sfd level (or member)
2408 0 macro FFAST CDIR3BUF = 972,0,0,0 %;
2409 0 literal FWASS CDIR3BUF = 39; ! subdirectory 2
2410 0 macro FFAST CDIR4BUF = 1011,0,0,0 %;
2411 0 literal FWASS CDIR4BUF = 39; ! subdirectory 3
2412 0 macro FFAST CDIR5BUF = 1050,0,0,0 %;
2413 0 literal FWASS CDIR5BUF = 39; ! subdirectory 4
2414 0 macro FFAST CDIR6BUF = 1089,0,0,0 %;
2415 0 literal FWASS CDIR6BUF = 39; ! subdirectory 5
2416 0 macro FFAST CDIR7BUF = 1128,0,0,0 %;
2417 0 literal FWASS CDIR7BUF = 39; ! subdirectory 6
2418 0 macro FFAST CDIR8BUF = 1167,0,0,0 %;
2419 0 literal FWASS_CDIR8BUF = 39; ! subdirectory 7
2420 0
2421 0 NOTES: 1. The following buffers must be contiguous as eventually the
2422 0 type and version are appended to the name string
2423 0
2424 0
2425 0 2. The name buffer and the type buffer must be 1 byte larger then
2426 0 the max name and type size (resp) because xpfm writes the
2427 0 name and type terminators in the buffer at the end of the string
2428 0
2429 0 macro FFAST NAMEBUF = 1206,0,0,0 %;
2430 0 literal FWASS NAMEBUF = 256; ! file name/quoted string buffer
2431 0 macro FFAST TYPEBUF = 1462,0,0,0 %;
2432 0 literal FWASS TYPEBUF = 40; ! file type buffer
2433 0 macro FFAST VERBUF = 1502,0,0,0 %;
2434 0 literal FWASS VERBUF = 6; ! file version buffer
2435 0 macro FFAST_UCBSTS = 1508,0,32,0 %; ! ucb$l_sts field for prim device
```


I 4
15-Sep-1984 22:56:58
15-Sep-1984 22:56:57

VAX-11 Bliss-32 V4.0-742
_S255SDUA28:[RMS.OBJ]RMSINTDEF.R32;1

Page 48
(9)

```
2435 0 macro FWASB_UNDER DEV = 1512,0,8,0 %; ! character "_" stored here
2436 0 macro FFAST_DEVICEBUF = 1513,0,0,0 %;
2437 0 literal FWASS_DEVICEBUF = 255; ! device name buffer
2438 0 macro FFAST_CDEVICEBUF = 1768,0,0,0 %;
2439 0 literal FWASS_CDEVICEBUF = 256; ! concealed device name buffer
2440 0 macro FWASB_UNDER NOD = 2024,0,8,0 %; ! character "_" stored here
2441 0 macro FFAST_NODEBUF = 2025,0,0,0 %;
2442 0 literal FWASS_NODEBUF = 127; ! node name buffer
2443 0 macro FFAST_WILD = 2152,0,0,0 %;
2444 0 literal FWASS_WILD = 48; ! scratch field used by RMOWILD
2445 0 size = count 1
2446 0 name 39
2447 0 .dir;* 6
2448 0 spare 2
2449 0 -----
2450 0 48
2451 0 macro FFAST_SHRFILBUF = 2200,0,0,0 %;
2452 0 literal FWASS_SHRFILBUF = 16; ! shared file device id buffer (readable form)
2453 0 macro FFAST_SHRFIL_LCKNAM = 2216,0,0,0 %;
2454 0 literal FWASS_SHRFIL_LCKNAM = 16; ! shared file device id buffer (unreadable form - used for lock name)
2455 0 macro FFAST_AS_SHRFILBUF = 2232,0,0,0 %;
2456 0 literal FWASS_AS_SHRFILBUF = 16; ! secondary device id buffer (readable form)
2457 0 macro FWASQ_BIJNL = 2248,0,0,0 %;
2458 0 literal FWASS_BIJNL = 8; ! descriptor of BI journal name
2459 0 macro FWASQ_AIJNL = 2256,0,0,0 %;
2460 0 literal FWASS_AIJNL = 8; ! descriptor of AI journal name
2461 0 macro FWASQ_ATJNL = 2264,0,0,0 %;
2462 0 literal FWASS_ATJNL = 8; ! descriptor of AT journal name
2463 0 macro FFAST_BIACE = 2272,0,0,0 %;
2464 0 literal FWASS_BIACE = 20; ! BI journal name ACE
2465 0 macro FFAST_BIJNLN = 2276,0,0,0 %;
2466 0 literal FWASS_BIJNLN = 16;
2467 0 macro FFAST_AIACE = 2292,0,0,0 %;
2468 0 literal FWASS_AIACE = 20; ! AI journal name ACE
2469 0 macro FFAST_AIJNLN = 2296,0,0,0 %;
2470 0 literal FWASS_AIJNLN = 16;
2471 0 macro FFAST_ATACE = 2312,0,0,0 %;
2472 0 literal FWASS_ATACE = 20; ! AT journal name ACE
2473 0 macro FFAST_ATJNLN = 2316,0,0,0 %;
2474 0 literal FWASS_ATJNLN = 16;
2475 0 macro FFAST_IDACE = 2332,0,0,0 %;
2476 0 literal FWASS_IDACE = 32; ! Journal ID ACE
2477 0 macro FFAST_JNLID = 2336,0,0,0 %;
2478 0 literal FWASS_JNLID = 28; ! complete journal ID
2479 0 macro FFAST_VOLNAM = 2336,0,0,0 %;
2480 0 literal FWASS_VOLNAM = 12; ! volume label of media file resides on
2481 0 macro FFAST_FID = 2348,0,0,0 %;
2482 0 literal FWASS_FID = 6; ! file-id
2483 0 macro FWASQ_ID_DATE = 2356,0,0,0 %;
2484 0 literal FWASS_ID_DATE = 8; ! id time stamp
2485 0
2486 0 !*** MODULE $SLBHDEF ***
2487 0
2488 0 SLBH - Search List Header Block
2489 0
2490 0 literal SLBH$C_BID = 43; ! ID
2491 0 literal SLBH$K_BLN = 20; ! length of SLBH
```



```

2492 0 literal SLB$C_BLN = 20; ! length of SLBH
2493 0 literal SLB$S_SLBDEF = 20;
2494 0 macro SLB$SL_FCINK = 0,0,32,0 %; ! forward link
2495 0 macro SLB$SL_BLINK = 4,0,32,0 %; ! backward link
2496 0 macro SLB$B_BID = 8,0,8,0 %; ! block ID
2497 0 macro SLB$B_BLN = 9,0,8,0 %; ! length
2498 0 macro SLB$B_PASSFLGS = 10,0,8,0 %; ! flags for FWA$B_PASSFLGS
2499 0 macro SLB$B_STR_LEN = 11,0,8,0 %; ! string length
2500 0 macro SLB$SL_SLB_QUE = 12,0,32,0 %; ! ptr to SLB queue
2501 0 macro SLB$SL_NAM_FNB = 16,0,32,0 %; ! saved FNB from RLF file
2502 0 macro SLB$T_STRING = 20,0,0,0 %; ! start of string
2503 0
2504 0 *** MODULE $SLBDEF ***
2505 0
2506 0 SLB - Search List Block
2507 0
2508 0 literal SLB$C_BID = 41; ! ID
2509 0 literal SLB$M_REALSLB = 1;
2510 0 literal SLB$K_BLN = 24; ! length of SLB
2511 0 literal SLB$C_BLN = 24; ! length of SLB
2512 0 literal SLB$S_SLBDEF = 24;
2513 0 macro SLB$SL_FCINK = 0,0,32,0 %; ! forward link
2514 0 macro SLB$SL_BLINK = 4,0,32,0 %; ! backward link
2515 0 macro SLB$B_BID = 8,0,8,0 %; ! block ID
2516 0 macro SLB$B_BLN = 9,0,8,0 %; ! length
2517 0 macro SLB$B_FLAGS = 10,0,8,0 %; ! flags
2518 0 macro SLB$V_REALSLB = 10,0,1,0 %; ! "Real" SLB as opposed to the fake FWA one
2519 0 macro SLB$B_LEVEL = 11,0,8,0 %; ! recursion level
2520 0 macro SLB$SL_INDEX = 12,0,32,0 %; ! translation index
2521 0 macro SLB$SL_MAX_INDEX = 16,0,32,0 %; ! max translation index
2522 0 macro SLB$SL_ATTR = 20,0,32,0 %; ! attributes flags
2523 0
2524 0 *** MODULE $FSCBDEF ***
2525 0
2526 0 FSCB - FileScan control block
2527 0
2528 0 This block is passed to PARSE_STRING from XPFN and RMS$FILESCAN
2529 0
2530 0
2531 0 The descriptors are defined as:
2532 0
2533 0 -----
2534 0 | flags | length |
2535 0 |-----|
2536 0 | address |
2537 0 |-----|
2538 0
2539 0
2540 0
2541 0 descriptor flags
2542 0
2543 0 These flags are used through out the RMS file name parsing routines.
2544 0 The flags can be found in all of the field descriptors.
2545 0
2546 0 NOTE: The flag ELIPS must be the first bit in the second word.
2547 0 It is referenced this way in RMOWILD and other places
2548 0

```


K 4
15-Sep-1984 22:56:58
15-Sep-1984 22:56:57

VAX-11 Bliss-32 V4.0-742 Page 50
_S255\$DUA28:[RMS.OBJ]RMSINTDEF.R32;1 (9)

```
2549 0 literal FSCBSM_ELIPS = 65536;
2550 0 literal FSCBSM_WILD = 131072;
2551 0 literal FSCBSM_ACS = 262144;
2552 0 literal FSCBSM_QUOTED = 524288;
2553 0 literal FSCBSM_NULL = 1048576;
2554 0 literal FSCBSM_PWD = 2097152;
2555 0 literal FSCBSM_GRPMBR = 4194304;
2556 0 literal FSCBSM_MINUS = 8388608;
2557 0 literal FSCBSM_CONCEAL = 16777216;
2558 0 literal FSCBSM_MFD = 33554432;
2559 0 literal FSCBSM_ROOTED = 67108864;
2560 0 literal FSCBS$FSCBDEF = 4;
2561 0 macro FSCBSV_ELIPS = 0,16,1,0 %;
2562 0 macro FSCBSV_WILD = 0,17,1,0 %;
2563 0 macro FSCBSV_ACS = 0,18,1,0 %;
2564 0 macro FSCBSV_QUOTED = 0,19,1,0 %;
2565 0 macro FSCBSV_NULL = 0,20,1,0 %;
2566 0 macro FSCBSV_PWD = 0,21,1,0 %;
2567 0 macro FSCBSV_GRPMBR = 0,22,1,0 %;
2568 0 macro FSCBSV_MINUS = 0,23,1,0 %;
2569 0 macro FSCBSV_CONCEAL = 0,24,1,0 %;
2570 0 macro FSCBSV_MFD = 0,25,1,0 %;
2571 0 macro FSCBSV_ROOTED = 0,26,1,0 %;
2572 0
2573 0 FSCB
2574 0
2575 0 literal FSCBSM_NODE = 1;
2576 0 literal FSCBSM_DEVICE = 2;
2577 0 literal FSCBSM_ROOT = 4;
2578 0 literal FSCBSM_DIRECTORY = 8;
2579 0 literal FSCBSM_NAME = 16;
2580 0 literal FSCBSM_TYPE = 32;
2581 0 literal FSCBSM_VERSION = 64;
2582 0 literal FSCBS$C_MAXNODE = 8;
2583 0 literal FSCBS$C_MAXROOT = 8;
2584 0 literal FSCBS$K_BLN = 260;
2585 0 literal FSCBS$C_BLN = 260;
2586 0 literal FSCBS$C_MAXDIR = 8;
2587 0 literal FSCBS$FSCBDEF1 = 260;
2588 0 macro FSCBSB_FCDFLAGS = 0,0,8,0 %;
2589 0 macro FSCBSV_NODE = 0,0,1,0 %;
2590 0 macro FSCBSV_DEVICE = 0,1,1,0 %;
2591 0 macro FSCBSV_ROOT = 0,2,1,0 %;
2592 0 macro FSCBSV_DIRECTORY = 0,3,1,0 %;
2593 0 macro FSCBSV_NAME = 0,4,1,0 %;
2594 0 macro FSCBSV_TYPE = 0,5,1,0 %;
2595 0 macro FSCBSV_VERSION = 0,6,1,0 %;
2596 0 macro FSCBSB_NODES = 1,0,8,0 %;
2597 0 macro FSCBSB_ROOTS = 2,0,8,0 %;
2598 0 macro FSCBSB_DIRS = 3,0,8,0 %;
2599 0 macro FSCBSQ_FILESPEC = 4,0,0,0 %;
2600 0 literal FSCBS$ FILESPEC = 8;
2601 0 macro FSCBSQ_NODE = 12,0,0,0 %;
2602 0 literal FSCBS$ NODE = 8;
2603 0 macro FSCBSQ_DEVICE = 20,0,0,0 %;
2604 0 literal FSCBS$ DEVICE = 8;
2605 0 macro FSCBSQ_ROOT = 28,0,0,0 %;
```

```
! elipssis was detected in directory (dir)
! a wild card was detected (dir,name,type,ver)
! access control string in node name (node)
! quoted file spec (name)
! field was null (terminator only) (all)
! password masked out (set in xpfm) (node)
! group,member format directory (dir)
! minus directory field (dir)
! name was concealed (dev)
! MFD directory (set in xpfm) (dir)
! directory was a root directory (dir)
```

```
! max number of node descriptors
! max number of root descriptors
```

```
! max number of directory descriptors
! field flags
```

```
! number of nodes in spec
! number of root directories in spec
! number of directories in spec
```

```
! full file spec
! full node list spec
! device spec
```


L 4
15-Sep-1984 22:56:58
15-Sep-1984 22:56:57

VAX-11 Bliss-32 V4.0-742
_S255SDUA28:[RMS.OBJ]RMSINTDEF.R32;1

Page 51
(9)

```
: 2606 0 literal FSCB$$ ROOT = 8; ! full root directory list spec
: 2607 0 macro FSCB$$ DIRECTORY = 36,0,0,0 %;
: 2608 0 literal FSCB$$ DIRECTORY = 8; ! full directory list spec
: 2609 0 macro FSCB$$ NAME = 44,0,0,0 %;
: 2610 0 literal FSCB$$ NAME = 8; ! file name
: 2611 0 macro FSCB$$ TYPE = 52,0,0,0 %;
: 2612 0 literal FSCB$$ TYPE = 8; ! file type
: 2613 0 macro FSCB$$ VERSION = 60,0,0,0 %;
: 2614 0 literal FSCB$$ VERSION = 8; ! file version
: 2615 0 macro FSCB$$ NODE1 = 68,0,0,0 %;
: 2616 0 literal FSCB$$ NODE1 = 8; ! the NODEn descriptors must be contiguous
: 2617 0 macro FSCB$$ NODE2 = 76,0,0,0 %;
: 2618 0 literal FSCB$$ NODE2 = 8;
: 2619 0 macro FSCB$$ NODE3 = 84,0,0,0 %;
: 2620 0 literal FSCB$$ NODE3 = 8;
: 2621 0 macro FSCB$$ NODE4 = 92,0,0,0 %;
: 2622 0 literal FSCB$$ NODE4 = 8;
: 2623 0 macro FSCB$$ NODE5 = 100,0,0,0 %;
: 2624 0 literal FSCB$$ NODE5 = 8;
: 2625 0 macro FSCB$$ NODE6 = 108,0,0,0 %;
: 2626 0 literal FSCB$$ NODE6 = 8;
: 2627 0 macro FSCB$$ NODE7 = 116,0,0,0 %;
: 2628 0 literal FSCB$$ NODE7 = 8;
: 2629 0 macro FSCB$$ NODE8 = 124,0,0,0 %;
: 2630 0 literal FSCB$$ NODE8 = 8;
: 2631 0 macro FSCB$$ ROOT1 = 132,0,0,0 %;
: 2632 0 literal FSCB$$ ROOT1 = 8; ! the ROOTn descriptors must be contiguous
: 2633 0 macro FSCB$$ ROOT2 = 140,0,0,0 %;
: 2634 0 literal FSCB$$ ROOT2 = 8;
: 2635 0 macro FSCB$$ ROOT3 = 148,0,0,0 %;
: 2636 0 literal FSCB$$ ROOT3 = 8;
: 2637 0 macro FSCB$$ ROOT4 = 156,0,0,0 %;
: 2638 0 literal FSCB$$ ROOT4 = 8;
: 2639 0 macro FSCB$$ ROOT5 = 164,0,0,0 %;
: 2640 0 literal FSCB$$ ROOT5 = 8;
: 2641 0 macro FSCB$$ ROOT6 = 172,0,0,0 %;
: 2642 0 literal FSCB$$ ROOT6 = 8;
: 2643 0 macro FSCB$$ ROOT7 = 180,0,0,0 %;
: 2644 0 literal FSCB$$ ROOT7 = 8;
: 2645 0 macro FSCB$$ ROOT8 = 188,0,0,0 %;
: 2646 0 literal FSCB$$ ROOT8 = 8;
: 2647 0 macro FSCB$$ DIRECTORY1 = 196,0,0,0 %;
: 2648 0 literal FSCB$$ DIRECTORY1 = 8; ! the DIRECTORYn descriptors must be contiguous
: 2649 0 macro FSCB$$ DIRECTORY2 = 204,0,0,0 %;
: 2650 0 literal FSCB$$ DIRECTORY2 = 8;
: 2651 0 macro FSCB$$ DIRECTORY3 = 212,0,0,0 %;
: 2652 0 literal FSCB$$ DIRECTORY3 = 8;
: 2653 0 macro FSCB$$ DIRECTORY4 = 220,0,0,0 %;
: 2654 0 literal FSCB$$ DIRECTORY4 = 8;
: 2655 0 macro FSCB$$ DIRECTORY5 = 228,0,0,0 %;
: 2656 0 literal FSCB$$ DIRECTORY5 = 8;
: 2657 0 macro FSCB$$ DIRECTORY6 = 236,0,0,0 %;
: 2658 0 literal FSCB$$ DIRECTORY6 = 8;
: 2659 0 macro FSCB$$ DIRECTORY7 = 244,0,0,0 %;
: 2660 0 literal FSCB$$ DIRECTORY7 = 8;
: 2661 0 macro FSCB$$ DIRECTORY8 = 252,0,0,0 %;
: 2662 0 literal FSCB$$_DIRECTORY8 = 8;
```



```

2663 0
2664 0
2665 0
2666 0
2667 0
2668 0
2669 0
2670 0
2671 0
2672 0
2673 0
2674 0
2675 0
2676 0
2677 0
2678 0
2679 0
2680 0
2681 0
2682 0
2683 0
2684 0
2685 0
2686 0
2687 0
2688 0
2689 0
2690 0
2691 0
2692 0
2693 0
2694 0
2695 0
2696 0
2697 0
2698 0
2699 0
2700 0
2701 0
2702 0
2703 0
2704 0
2705 0
2706 0
2707 0
2708 0
2709 0
2710 0
2711 0
2712 0
2713 0
2714 0
2715 0
2716 0
2717 0
2718 0
2719 0

*** MODULE $SWBDEF ***

Directory string work buffer for wild card directory processing

literal SWB$M_ELLIPSIS = 1;
literal SWB$M_BOUNDED = 2;
literal SWB$M_WILD = 4;
literal SWB$M_DELIMITER = 8;
literal SWB$M_TRAVERSE = 16;
literal SWB$M_FIRST = 32;
literal SWB$M_ELLIPSIS_EXISTS = 64;
literal SWB$M_VALID_DID = 128;
literal SWB$C_BID = 42; ! ID
literal SWB$K_BLN = 328;
literal SWB$C_BLN = 328;
! wild dir spec
literal SWB$S_SWBDEF = 328;
macro SWB$B_FLAGS = 0,0,8,0 %; ! flags (must be first)
macro SWB$V_ELLIPSIS = 0,0,1,0 %; ! ellipsis
macro SWB$V_BOUNDED = 0,1,1,0 %; ! ellipsis bounded
macro SWB$V_WILD = 0,2,1,0 %; ! wild name
macro SWB$V_DELIMITER = 0,3,1,0 %; ! following delimiter
macro SWB$V_TRAVERSE = 0,4,1,0 %; ! should skip subtree
macro SWB$V_FIRST = 0,5,1,0 %; ! first time through
macro SWB$V_ELLIPSIS_EXISTS = 0,6,1,0 %; ! dir spec contains ...
macro SWB$V_VALID_DID = 0,7,1,0 %; ! FIB DID is valid
macro SWB$B_PATLEN = 1,0,8,0 %; ! length of current token
macro SWB$B_PPOS = 2,0,8,0 %; ! position in pattern
macro SWB$B_TOKENS_LEFT = 3,0,8,0 %; ! number of non ... tokens left
macro SWB$B_MINIMUM = 4,0,8,0 %; ! minimum level for success
macro SWB$B_MAXIMUM = 5,0,8,0 %; ! maximum level for success
macro SWB$B_FIRST_E = 6,0,8,0 %; ! token ! of first ellipsis
macro SWB$B_DIRWCFLGS = 7,0,8,0 %; ! FW$B_DIRWCFLGS on entry
macro SWB$B_BID = 8,0,8,0 %; ! block ID
macro SWB$B_BLN = 9,0,8,0 %; ! length
macro SWB$Q_PATTERN = 12,0,0,0 %;
literal SWB$S_PATTERN = 8; ! descriptor of pattern
macro SWB$S_SCRATCH_PAT = 20,0,32,0 %; ! scratch copy of first longword
macro SWB$S_SCRATCH_BUF = 24,0,0,0 %;
literal SWB$S_SCRATCH_BUF = 48; ! scratch temp buffer (same size as FW$T_WILD)
macro SWB$T_PATTERN_BUF = 72,0,0,0 %;
literal SWB$S_PATTERN_BUF = 256; ! should be: FW$C_MAXDIRLEN-2,

*****
*
* Copyright (c) 1982, 1983
* by DIGITAL Equipment Corporation, Maynard, Mass.
*
* This software is furnished under a license and may be used and copied
* only in accordance with the terms of such license and with the
* inclusion of the above copyright notice. This software or any other
* copies thereof may not be provided or otherwise made available to any
* other person. No title to and ownership of the software is hereby
* transferred.
*
* The information in this software is subject to change without notice

```


N 4
15-Sep-1984 22:56:58
15-Sep-1984 22:56:57


VAX-11 Bliss-32 V4.0-742
_S255SDUA28:[RMS.OBJ]RMSINTDEF.R32;1

Page 53
(9)

NT
VO

```
2720 0 | * and should not be construed as a commitment by DIGITAL Equipment *
2721 0 | * Corporation. *
2722 0 | *
2723 0 | * DIGITAL assumes no responsibility for the use or reliability of its *
2724 0 | * software on equipment which is not supplied by DIGITAL. *
2725 0 | *
2726 0 | *****
2727 0 | *****
2728 0 | Created 15-SEP-1984 22:54:43 by VAX-11 SDL V2.0 Source: 15-SEP-1984 22:49:34 _S255SDUA28:[RMS.SRC]RMSSHR.
2729 0 | *****
2730 0
2731 0
2732 0 | *** MODULE $SFSBDEF ***
2733 0 | literal SFSB$C_BID = 16; | sfsb code
2734 0 | literal SFSB$C_FIX_LEN = 10; | 10 bytes of fixed size data
2735 0 | literal SFSB$K_BLN = 68; | length of sfsb
2736 0 | literal SFSB$C_BLN = 68; | length of sfsb
2737 0
2738 0 | keep the next two fields in same order as they are in FAB
2739 0
2740 0 | literal SFSB$$SFSBDEF = 68;
2741 0 | macro SFSB$Q_FILENAME = 0,0,0,0 %;
2742 0 | literal SFSB$$FILENAME = 8; | descriptor of shared file resource name.
2743 0 | resource name is NODE, DEVICE, FILE_ID
2744 0 | points to RESNAM, below
2745 0 | macro SFSB$W_NAME_LEN = 0,0,16,0 %; | subfield to address descriptor length field
2746 0 | macro SFSB$L_ADDRESS = 4,0,32,0 %; | subfield to address descriptor address field
2747 0 | macro SFSB$B_BID = 8,0,8,0 %; | block id
2748 0 | macro SFSB$B_BLN = 9,0,8,0 %; | block length in longwords
2749 0 | macro SFSB$B_CURMODE = 10,0,8,0 %; | Mode of the current lock
2750 0 | macro SFSB$B_PREMODE = 11,0,8,0 %; | Mode of the previous lock
2751 0 | macro SFSB$T_RESNAM = 12,0,0,0 %;
2752 0 | literal SFSB$$RESNAM = 32; | 32 bytes for name of shared resource
2753 0 | macro SFSB$L_FAC_CODE = 12,0,32,0 %; | RMS facility code (RMS$)
2754 0 | macro SFSB$W_FID_NUM = 16,0,16,0 %; | file id word one
2755 0 | macro SFSB$W_FID_SEQ = 18,0,16,0 %; | file id word two
2756 0 | macro SFSB$W_FID_RVN = 20,0,16,0 %; | file id word three
2757 0 | macro SFSB$T_DEV_NAM = 22,0,0,0 %;
2758 0 | literal SFSB$$DEV_NAM = 22; | 22 bytes remain to hold device id (node$device_name)
2759 0 | macro SFSB$L_LRSB = 44,0,32,0 %; | lock status block
2760 0 | macro SFSB$W_STATUS = 44,0,16,0 %; | VMS status code
2761 0 | macro SFSB$W_S_BITS = 46,0,16,0 %; | various status bits
2762 0 | macro SFSB$L_LOCK_ID = 48,0,32,0 %; | second longword of LKSB is the lock id
2763 0 | macro SFSB$L_LVB = 52,0,0,0 %;
2764 0 | literal SFSB$$LVB = 16; | lock value block
2765 0 | macro SFSB$B_FAC = 52,0,8,0 %; | fac bits from FAB
2766 0 | macro SFSB$B_SHR = 53,0,8,0 %; | sharing bits (from FAB SHR field)
2767 0 | macro SFSB$L_HBK = 60,0,32,0 %; | high block
2768 0 | macro SFSB$L_EBK = 64,0,32,0 %; | end of file
2769 0
2770 0 | *** MODULE $GBSBDEF ***
2771 0
2772 0 | GBSB field definitions - global buffer synchronization block
2773 0
2774 0 | The GBSB contains the information necessary to determine if a
2775 0 | global section is already open for a file on a given node, and
2776 0 | is used for synchronizing access to the global section.
```


gbsb:



lksb:

lkvb:

```

literal GBSB$C_BID = 9;          ! gbsb code
literal GBSB$M_NOTACCESSED = 1;
literal GBSB$K_BLN = 68;         ! length of gbsb
literal GBSB$C_BLN = 68;         ! length of gbsb
literal GBSB$S_GBSBDEF = 68;
macro GBSB$Q_FILENAME = 0,0,0,0 %;
literal GBSB$S_FILENAME = 8;     ! descriptor of shared file resource name.
! resource name is NODE, DEVICE, FILE_ID
! points to RESNAM, below
macro GBSB$W_NAME_LEN = 0,0,16,0 %; ! subfield to address descriptor length field
macro GBSB$L_ADDRESS = 4,0,32,0 %; ! subfield to address descriptor address field
macro GBSB$B_BID = 8,0,8,0 %;      ! block id
macro GBSB$B_BLN = 9,0,8,0 %;      ! block length in longwords
macro GBSB$B_CURMODE = 10,0,8,0 %; ! Mode of the current lock
macro GBSB$B_FLAGS = 11,0,8,0 %;   ! spare
macro GBSB$V_NOTACCESSED = 11,0,1,0 %; ! Process has already decremented access count for GBS.
macro GBSB$T_RESNAM = 12,0,0,0 %;
literal GBSB$S_RESNAM = 32;        ! 32 bytes for name of shared resource
macro GBSB$L_LRSB = 44,0,32,0 %;   ! lock status block
macro GBSB$W_STATUS = 44,0,16,0 %; ! VMS status code
macro GBSB$W_S_BITS = 46,0,16,0 %; ! various status bits
macro GBSB$L_LOCK_ID = 48,0,32,0 %; ! second longword of LKSB is the lock id
macro GBSB$W_GBC = 52,0,16,0 %;    ! Number of global buffers in section.
macro GBSB$W_GBREF = 54,0,16,0 %;  ! Number of accessors to global section.
macro GBSB$L_GS_SIZE = 56,0,32,0 %; ! Size of global section in bytes.

```

Version: 'V04-000'

*

C 5
15-Sep-1984 22:56:58
15-Sep-1984 22:56:57

VAX-11 Bliss-32 V4.0-742
_S255SDUA28:[RMS.OBJ]RMSINTDEF.R32;1

















































































































































































































































































Page 55
(9)

```
: 2834 0  ! * COPYRIGHT (c) 1978, 1980, 1982, 1984 BY
: 2835 0  ! * DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.
: 2836 0  ! * ALL RIGHTS RESERVED.
: 2837 0  ! *
: 2838 0  ! * THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED
: 2839 0  ! * ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE
: 2840 0  ! * INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER
: 2841 0  ! * COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY
: 2842 0  ! * OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY
: 2843 0  ! * TRANSFERRED.
: 2844 0  ! *
: 2845 0  ! * THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE
: 2846 0  ! * AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT
: 2847 0  ! * CORPORATION.
: 2848 0  ! *
: 2849 0  ! * DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS
: 2850 0  ! * SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.
: 2851 0  ! *
: 2852 0  ! *
: 2853 0  ! *****
: 2854 0  !
: 2855 0  ! ++
: 2856 0  ! UTLDEF_UNDECLARE.R32 - undeclare macros defined in UTLDEF.R32.
: 2857 0  ! --
: 2858 0  !
: 2859 0  UNDECLARE %QUOTE $BYTEOFFSET;
: 2860 0  UNDECLARE %QUOTE $BITPOSITION;
: 2861 0  UNDECLARE %QUOTE $FIELDWIDTH;
: 2862 0  UNDECLARE %QUOTE $EXTENSION;
: 2863 0  UNDECLARE %QUOTE $FIELDMASK;
: 2864 0  UNDECLARE %QUOTE $EQLST;
: 2865 0  UNDECLARE %QUOTE GET2ND_;
: 2866 0  UNDECLARE %QUOTE NUL2ND_;
: 2867 0  UNDECLARE %QUOTE GET1ST_;
```

COMMAND QUALIFIERS

```
:
: BLISS/LIB=LIB$:RMSINTDEF/LIS=LISS$:RMSINTDEF.LST LIB$:RMSINTDEF
: Run Time: 00:17.4
: Elapsed Time: 00:19.9
: Lines/CPU Min: 9908
: Lexemes/CPU-Min: 62899
: Memory Used: 292 pages
: Library Precompilation Complete
```

NT
VO

0315 AH-BT13A-SE
VAX/VMS V4.0

DIGITAL EQUIPMENT CORPORATION
CONFIDENTIAL AND PROPRIETARY

NT0ACCESS
LIS

NT0CLOSE
LIS

NT0BLDXAB
LIS

NT0CONN
LIS

NT0CREATE
LIS

NT0DAP10
LIS

NT0DAPCRC
LIS

NT0ACCFIL
LIS

NT0BLK10
LIS